



WALLTILE	
WHITE LR94	ALMOND LR95



LARGO[™] GLAZED CERAMIC



SIZES

		Thickness	Sq. Ft. per Carton	Pieces per Carton
6 x 6 Wall Tile	(6" x 6") (15.20 cm x 15.20 cm)	5/16"	12.50	50
4-1/4 x 4-1/4 Wall Tile	(4-1/4" x 4-1/4") (10.80 cm x 10.80 cm)	5/16"	12.50	100
3 x 6 Wall Tile	(3" x 6") (7.62 cm x 15.20 cm)	5/16"	12.50	100

APPLICATIONS

ALLECATIONS	
	Suitable
Floors	
Walls/Backsplashes	✓
Countertops	
Pool Linings	✓

APPLICATION NOTES:

Suitable for exterior wall applications in non-freezing climates only when proper installation methods are followed.

INSTALLATION

C	Grout Joint Recommendation	Shade Variation
	1/16"	Low (V1)

TRIM

	Туре	Number	Size	Pieces per Carton
	Wall Bullnose	S-4369 (6" side)	3 x 6	100
	Wall Bullnose Corner	SN-4339	3 x 3	24
	Wall Bullnose	S-4269 (6" side)	2 x 6	100
	Wall Bullnose Corner	SN-4269	2 x 2	25
	Radius Bullnose	A-4200	2 x 6	64
0	Radius Bullnose Corner	AN-4200	2 x 2	18
	Quarter Round	A-106	1 x 6	180
\bigcirc	Quarter Round Corner	UC-106	1 x 1	40

TEST RESULTS

	ASTM#	Wall Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120-230 lbs
Scratch Hardness	MOHS	4.0-6.0
Chemical Resistance	C650	Resistant

NOTES

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at daltile.com/Factors.





