



FLOOR

FABRIQUE™
COLORBODY™ PORCELAIN

 **daltile®**
IMAGINE WHAT'S POSSIBLE™



Cover photo featured in THE NEW AMERICAN HOME.
Photo features Fabrique™ Noir Linen 12 x 24 floor tile and 2 x 2 mosaic on shower wall.
Above photo featured in THE NEW AMERICAN HOME.
Photo features Fabrique™ Soleil Linen 24 x 24 unpolished on the floor.

Create a Design with a Delicate Fabric Touch

Fabrique combines the detail of fine fabrics with porcelain flooring that creates an atmosphere as rich and intricate as handcrafted linen. Taking cues from different textures and colors, the Fabrique collection draws inspiration from the way fabric moves and allows you to bring a delicate elegance to any space.

- **TEXTURAL INSPIRATION**
 - Inspired by the flow of fabric
 - Fabric visual adds a delicate elegance to design
- **ELEGANT DESIGN OPTIONS**
 - Linear pattern ideal for designs that call for a continuous look
 - Large-format and linear sizes available for more design options



**PRE-CONSUMER
RECYCLED MATERIALS**



LINEAR OPTIONS




TRU-EDGE

All or select items within this series meet the requirements for these qualifications. For more product information, visit daltile.com.



FLOOR TILE



SOLEIL LINEN P687



Close-up
of tile




BLANC LINEN P685



CRÈME LINEN P686



GRIS LINEN P690



BRUN LINEN P691



NOIR LINEN P689

FLOOR




FABRIQUE™

COLORBODY™ PORCELAIN

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	24 x 24 Floor Tile (Unpolished)	(23-7/16" x 23-7/16") (59.44 cm x 59.44 cm)	3/8"	15.28	4
	12 x 24 Floor Tile (Light Polished & Unpolished)	(11-5/8" x 23-7/16") (29.56 cm x 59.44 cm)	3/8"	15.28	8
	12 x 12 Floor Tile (Unpolished)	(11-5/8" x 11-5/8") (29.56 cm x 29.56 cm)	3/8"	10.23	11
	2 x 2 Mosaic (Unpolished) (Mesh-mounted on 12 x 12 Sheet)	(11-5/8" x 11-5/8") Sheet (29.56 cm x 29.56 cm Sheet)	3/8"	11.40	12

LINEAR OPTIONS™ SIZES

			Sq. Ft. per Carton	Pieces per Carton
	6 x 24 Floor Tile	(5-3/4" x 23-7/16") (14.63 cm x 59.44 cm)	10.65	11
	4 x 24 Floor Tile	(3-13/16" x 23-7/16") (9.73 cm x 59.44 cm)	6.46	10
	2 x 24 Floor Tile	(1-13/16" x 23-7/16") (4.67 cm x 59.44 cm)	6.66	20

Additional linear and rectangular sizes available through Linear Options™, Daltile's linear cutting service. Visit daltile.com/LinearOptions for size and order information.

FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓*
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	✓**


APPLICATION NOTES:

* Unpolished surface only. Floor tile and mosaic suitable. Mosaic also suitable for residential and light commercial shower floors.

** Mosaic only

Suitable for exterior applications in freezing and non-freezing climates when proper


TRIM

Type	Number	Size	Pieces per Carton
 Bullnose (Light Polished & Unpolished)	S-43C9	3 x 12	30

Bullnose trim is intended to coordinate with floor tile in the standard 90-degree installation position.

Bullnose also available in horizontal design in all colors via Special Order.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%)	 Medium (V2)

TEST RESULTS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

NOTES

Manufacturer Advisory: The light polished tiles have a dynamic coefficient of friction < 0.42 as measured by the DCOF Acutest method. Tiles with DCOF values < 0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at www.tileusa.com.

Special consideration must be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltile.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltilegreenworks.com.



SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GET.DALTILE.COM



7834 C. F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2017 Daltile (2/17)