



STONE LOOK

FLOOR | WALL
BRICKWORK™
GLAZED PORCELAIN



 **daltile®**
IMAGINE WHAT'S POSSIBLE™

FLOOR | WALL

BRICKWORK™

GLAZED PORCELAIN

Create Your Own Urban Revival

Renew your space with the dramatic look of Brickwork™. This modern twist on trend favorite uses random shade variation and distressed edges to emulate brick traditionally found in historic metropolitan architecture and design. Brickwork is ideal for adding warmth, texture and a historic feel to a room. With its size options and diverse color palette, Brickwork is the ideal product to add an urban touch to your space.

• URBAN VISUAL

- Shade variation, distressed edges and weathering texture emulate the look of antique brick
- Adds warm, historic feel to rooms
- Visual reminiscent of exposed brick commonly found in urban architecture

• HISTORIC OPTIONS

- Two sizes available that can be used together to create authentic designs
- Offered in six colors to complement multiple design styles

STONE
LOOK

USAGE



SPECIAL FEATURES

SEE CHARTS FOR FULL
PRODUCT DETAILS

Cover photo features Studio 4 x 8 in a brick-joint pattern on the wall and Yorkwood Manor™ Birchtree on the floor. Above photo features Terrace 2 x 8 field tile in a brick-joint pattern on the wall and Season Wood™ Redwood Grove on the floor.

SIZES:

□ 4 x 8 Floor Tile □ 2 x 8 Floor Tile

FINISHES: MATTE

2 x 8 FLOOR TILE



STUDIO BW01



ATRIUM BW02



PATIO BW03



ALCOVE BW04



TERRACE BW05



CORRIDOR BW06

4 x 8 FLOOR TILE



STUDIO BW01



ATRIUM BW02



PATIO BW03



ALCOVE BW04



TERRACE BW05



CORRIDOR BW06



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT™
*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT™
*Not Applicable to Mesh-Mounted Mosaics





CLIMATEPRO™



SIMPLICLEAN™

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	4 x 8 Floor Tile	(3-7/8" x 8") (9.84 cm x 20.34 cm)	3/8"	7.92	36
	2 x 8 Floor Tile	(2-1/4" x 8") (5.73 cm x 20.34 cm)	3/8"	4.68	36

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/8"	 Random (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

NOTES

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltile.com/Factors.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.