

## FIELD TILE



CANDIDO CA22



CREMA CA20



LIGHT NOCE CA21



MASSO CA23

## Style Meets Durability

Create a fresh, updated look in any space with Cannes. With an unpolished surface and smooth stone visual, Cannes offers both style and durability.

- **RENEWED PRESENCE**
  - Features an unpolished surface and smooth stone visual
  - Ideal for creating an updated look
- **FUNCTIONAL STYLE**
  - Offered in three versatile sizes
  - Design suits multiple décor preferences



**PRE-CONSUMER RECYCLED MATERIALS**



**MADE IN THE U.S.A.**



**REVEAL IMAGING®**

All or select items within this series are made in the USA. For more information, visit [daltile.com/Cannes](http://daltile.com/Cannes).

**SIZES**

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	12 x 24 Field Tile	(11-9/16" x 23-3/8") (29.40 cm x 59.30 cm)	3/8"	15.04	8
	18 x 18+ Field Tile	(17-1/2" x 17-1/2") (44.45 cm x 44.45 cm)	5/16"	17.04	8
	12 x 12+ Field Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	14.55	15

+ This product is manufactured regionally. Slight variances in size and shading may occur between regions. Please contact your sales representative to verify carton square footage. As with all tile projects, be sure to purchase sufficient quantities with your initial order.

**FLOOR APPLICATIONS**

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).


**OTHER APPLICATIONS**

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	

**APPLICATION NOTES:**


Suitable for exterior applications in non-freezing climates only when proper installation methods are followed.

**TRIM**

Type	Number	Size	Pieces per Carton
 Bullnose	P-43C9	3 x 12	22

Bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

**INSTALLATION**

Grout Joint Recommendation	Shade Variation
3/16" (when tile with a length greater than 15" is installed in a staggered brick-joint pattern, overlap should not exceed 33%)	 Medium (V2)

**TEST RESULTS**

	ASTM#	Result
Water Absorption	C373	< 7.0%
Breaking Strength	C648	> 250 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	3

For additional information, visit [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

**NOTES**

**Manufacturer Advisory:** These tiles have a dynamic coefficient of friction < 0.42 as measured by the DCOF Acutest method. Tiles with DCOF values < 0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at [www.tileusa.com](http://www.tileusa.com).

Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at [daltile.com/Factors](http://daltile.com/Factors).



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit [daltilegreenworks.com](http://daltilegreenworks.com).



SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: [GET.DALTILE.COM](http://GET.DALTILE.COM)



7834 C. F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at [daltile.com](http://daltile.com).



IMAGINE WHAT'S POSSIBLE™

©2016 Dal-Tile Corporation (10/16)