



FLOOR

**COTTO CONTEMPO™**  
GLAZED PORCELAIN with REVEAL IMAGING®

 **daltile®**  
IMAGINE WHAT'S POSSIBLE™





Coverphoto features WallStreet 12 x 24 field tile on the floor.  
Above photo features Michigan Avenue 20 x 20 field tile on the floor.

## A Sophisticated, Modern Take on Classic Cotto

Expansive as it is stunning, this gorgeous, upscale glazed porcelain marries a bold cotto look with elements of cracked cement. Equally at home in an urban loft or country villa, Cotto Contempo's™ contemporary, large-format tiles are a great choice for floors, walls, countertops and more. With its earthy, dimensional hues and multi-faceted color variance, Cotto Contempo offers stunning, modern style in four colors.

- **STYLISH COTTO LOOK WITH A TWIST**
  - Fresh contemporary look combines traditional cotto with elements of cracked cement
  - Four color options offer a high level of variation and color depth for a rich, earthy appearance

 **PRE-CONSUMER RECYCLED MATERIALS**

 **MADE IN THE U.S.A.**

 **REVEAL IMAGING®**

All or select items within this series are made in the USA. For more information, visit [daltile.com/CottoContempo](http://daltile.com/CottoContempo).

 **CERTIFIED PORCELAIN TILE**  
© 2014 Daltile of North America, Inc.



# COTTO CONTEMPO™

GLAZED PORCELAIN with REVEAL IMAGING®

## FIELD TILE



PENNSYLVANIA AVENUE CC12



W ALL STREET CC13



SUNSET BOULEVARD CC15







MICHIGAN AVENUE CC14

# COTTO CONTEMPO™

GLAZED PORCELAIN with REVEAL IMAGING®

## SIZES

			Thickness	Sq.Ft. per Carton	Pieces per Carton
	12 x 24 Field Tile	(11-13/16" x 23-5/8") (30.00 cm x 60.00 cm)	3/8"	11.58	6
	20 x 20 Field Tile	(19-11/16" x 19-11/16") (50.00 cm x 50.00 cm)	3/8"	16.14	6
	13 x 13 Field Tile	(13-1/8" x 13-1/8") (33.33 cm x 33.33 cm)	5/16"	17.85	15
	6-1/2 x 6-1/2 Field Tile	(6-9/16" x 6-9/16") (16.70 cm x 16.70 cm)	5/16"	10.80	36

## FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level- Interior	N/A	✓
Wet & Level- Interior	0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	0.60	
Ramps & Inclines	0.65	

A DCOF value of 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A 1371-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest®, visit [daltille.com/DCOF](http://daltille.com/DCOF).

## OTHER APPLICATIONS




	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	✓*

### APPLICATION NOTES:

\* 6-1/2 x 6-1/2 field tile only

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.


## TRIM

	Type	Number	Size	Pieces Per Carton
	Bulnosc	P-43E9	3 x 13	30
	Cove Base V	P-36E9TB	6 x 13	22
	Cove Base Corner V	PC-36E9TB	1 x 6	15

Floorbulnosc, cove base and cove base corner trim are intended to coordinate with floor field tile in the standard 90-degree installation position.

V Cove base and corner are clay body ceramic suitable for exterior applications in non-freezing climates only.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16" overlap should not exceed 33% when installing in a staggered brick-joint pattern)	 High (V3)

## TEST RESULTS

	ASTM #	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 400 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	4 (CC12 only) 3 (CC13-CC15)

For additional info, visit [daltille.com/information/TestResults](http://daltille.com/information/TestResults).

## NOTES

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [daltille.com/LargeTiles](http://daltille.com/LargeTiles) for more information.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tile and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A 137.1 standards.

Water, oil, grease, etc. create slippery conditions. For applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information, refer to "Factors to Consider" at [daltille.com/Factors](http://daltille.com/Factors).



DESIGNED TO HELP EARN LEED™ CREDITS. Form one detailed information, visit [daltillegreenworks.com](http://daltillegreenworks.com).

SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: [GETDALTILE.COM](http://GETDALTILE.COM)



7834 C.F. Hawin Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltille® products and information, visit our website at [daltille.com](http://daltille.com).



IMAGINE WHAT'S POSSIBLE™

© 2016 Dal-Tile Corporation (7/16)