

WALL

COMPOSITION™  
GLAZED CERAMIC



 daltile®  
IMAGINE WHAT'S POSSIBLE®

# COMPOSITION™

GLAZED CERAMIC

## Created for a Dramatic Finish

Make your room a work of art with Composition tile. Its matte and glossy neutral colors attract architects, designers, builders and homeowners alike. Use the large 12 x 24 size to create grand statements and impressive accent walls. With its crisp graphic and Tru-Edge™ formatting, Composition is the ideal wall tile for creating dramatic spaces.



Cover photo features Gesso Matte 12 x 24 wall tile.  
Above photo features Visionary Gloss 12 x 24 wall tile.



WALL

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



REVEAL SYNC3D™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



GLAZED CERAMIC



LOW HIGH

SEE CHARTS FOR FULL PRODUCT DETAILS

SPECIAL FEATURES

SIZES:



FINISHES: MATTE | GLOSSY


COLOR PALETTE



VISIONARY



PROVIDENTIAL



GESSO


WALL TILE



VISIONARY GLOSS CP05



PROVIDENTIAL GLOSS CP06



GESSO GLOSS CP01 / GESSO MATTE CP02

JOLLY TRIM



VISIONARY GLOSS CP05



PROVIDENTIAL GLOSS CP06



GESSO GLOSS CP01 / GESSO MATTE CP02



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT\*  
\*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT



SIMPLICLEAN™

# COMPOSITION™

GLAZED CERAMIC

WALL

## SIZES

		Thickness
	12 x 24 Wall Tile	(12" x 24") (30.00 cm x 60.00 cm)
		3/8" 9.30mm

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors - Standard Center Drain (Residential or Commercial)	≥ 0.42	
Shower Floors - Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest<sup>+</sup>, visit [daltille.com/DCOF](http://daltille.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

## TRIM

Type	Number	Size
 12" Jolly	S1/212J	1/2 x 12

## INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (when installing in a staggered brick-joint pattern; overlap should not exceed 33%)	 Low (V1)*
	 High (V3)**
* Applies to colors CP01 & CP02 only.	
** Applies to colors CP05 & CP06 only.	

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20%
Breaking Strength	C648	120 - 230lbs
Scratch Hardness	MOHS	4.0-6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [daltille.com/information/TestResults](http://daltille.com/information/TestResults).

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [daltille.com/LargeTiles](http://daltille.com/LargeTiles) for more information.

For additional information refer to "Factors to Consider" at: [daltille.com/Factors](http://daltille.com/Factors).



All or select items within this series meet the requirements for these qualifications. For more information, visit [daltille.com](http://daltille.com).



Healthy Homes | Healthy Planet

7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltille® products and information, visit our website at [daltille.com](http://daltille.com).



IMAGINE WHAT'S POSSIBLE™

©2024 Daltille (11/24)