STONE LOOK

17

# DIGNITARY™

STONE ATTACHÉ<sup>™</sup> COLLECTION - COLORBODY<sup>™</sup> PORCELAIN



# DIGNITARY™

STONE ATTACHÉ<sup>™</sup> COLLECTION - COLORBODY<sup>™</sup> PORCELAIN

## Ageless and Innovative – the Dignitary<sup>™</sup> Series

The imaginative Dignitary Series provides depth on surfaces as it replicates French limestone embedded with fossil layers and natural veins. Beautiful in any setting, this outstanding ColorBody" porcelain tile is equally suited to traditional or contemporary styles, bringing ageless dimension to every application. An array of colors in matte finish are available in three largeformat sizes and a coordinating mosaic. Polished and textured finishes, as well as a 2 cm thickness, are also available in select sizes.

- REIMAGINING A CLASSIC
  - Small fossils and veining replicate the look of French limestone that has stood the test of time
  - A collection of rich neutral colors appeal to contemporary tastes
  - 2 cm thick paver tile available in 24 x 24 size and three colors
- AGELESS BEAUTY ANYWHERE
  - Three finishes offer the ability to stretch designs from floors to walls, indoors, and out
  - Three large-format sizes plus an abstract mosaic all provide dimensional depth



Cover photo features Dignitary" Superior Taupe 24 x 48 on the floor, Superior Taupe 12 x 24 on the left wall, Luminary White 12 x 24 on the right wall, and Superior Taupe abstract mosaic on the shower wall. Above photo features Dignitary" Superior Taupe 24 x 48 on the floor and Luminary White 12 x 24 on the wall. NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODU<u>CT DETAILS</u>

STONE

LOOK

FLOOF

Ð

# DIGNITARY™

STONE ATTACHÉ<sup>™</sup> COLLECTION - COLORBODY<sup>™</sup> PORCELAIN





LUMINARY WHITE DR07\*





EMINENCE GREY DR10



SUPERIOR TAUPE DR08\*



LUMINARY WHITE DR07



ABSTRACT MOSAIC - Available in Matte only

NOTABLE BEIGE DR09



EMINENCE GREY DR10



SUPERIOR TAUPE DR08



GOVERNOR BLACK DR11









ANT' FIRE-RESISTANT' and 'Not Applicable to Mesh-Mounted



Available in 2 cm thickness in 24 x 24 size

SIMPLICLEAN"

VISIT THE WHY TILE PAGE AT WWW.DALTILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

# DIGNITARY™

## STONE ATTACHÉ<sup>™</sup> COLLECTION - COLORBODY<sup>™</sup> PORCELAIN

SIZES

OILLO					
			Thickness		Pieces/ Carton
	24 x 48 <b>*</b> Floor Tile	(23-3/8" x 46-15/16") 59.44 cm x 119.20 cm	7/16"	15.50	2
	24 x 24 ∎ Paver Tile	(23-3/8" x 23-3/8") (59.44 cm x 59.44 cm)	13/16'' (2cm)	7.60	2
	24 x 24 <b>*</b> Floor Tile	(23-3/8" x 23-3/8") (59.44 cm x 59.44 cm)	5/16"	15.20	4
	12 x 24 Floor Tile	(11-5/8" x 23-3/8") (29.56 cm x 59.44 cm)	5/16"	17.02	9
	6 x 24 Floor Tile*	(5-3/4" x 23-3/8") 14.61 cm x 59.44 cm	5/16"	10.23	11
	Abstract * Mosaic (Mesh Mounted)	(12" x 12" Sheet) (30.48 cm x 30.48 cm Sheet)	5/16"	3.88	4

✤ Available in Matte only

Available in 2cm thickness with textured surface in DR07, DR08 and DR09 colors only

\* Avaliable through Daltile's Linear Options program

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	<ul> <li>Image: A start of the start of</li></ul>
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓**
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	<b>V</b> ***
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	~
Countertops	N/A	~
Pool Linings	N/A	<b>v</b> **

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest<sup>™</sup>, visit daltile.com/DCOF.

## APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

- \* Matte and Textured only
- \*\* Mosaic tile only
- \*\*\* Textured and paver tile only

PRE-CONSUMER RECYCLED MATERIALS



## **REVEAL IMAGING®**

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.





## TRIM

	Туре	Number	Size	Pieces/ Carton
$\bigcirc$	Bullnose	P43F9	3 x 24	10
	Cove Base	S36C9	6 x 12	22
	Cove Base Outcorner	SC36C9	1 x 6	15

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

## INSTALLATION

## Grout Joint Recommendation Shade Variation Floor: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.) Random (V4)

### Mosaic: 1/8"

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs > 1000 lbs (2 cm)
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

## DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	3	All Residential / Light Commercial

2	All Residential Areas	(4	) All Residential / Commerce	cial

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A1371 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Manufacturer Advisory: All tile is measured by the DCOF AcuTest™ method. Tiles with DCOF values <0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at www.tileusa.com.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

7834 C.F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



STONE LOOK

# XTERIORS<sup>M</sup>

# ву 🔪 daltile

DIGNITARY COLORBODY<sup>™</sup> PORCELAIN PAVERS

> TREAD PORCELAIN PAVERS

## DIGNITARY<sup>™</sup> COLORBODY<sup>™</sup> PORCELAIN PAVERS

# Ageless Innovation

The imaginative Dignitary Series provides depth on surfaces as it replicates French limestone embedded with fossil layers and natural veins. Beautiful as it is strong, this outstanding ColorBody<sup>®</sup> porcelain 2CM paver tile is equally suited to traditional or contemporary styles, bringing ageless dimension to any outdoor application. An array of colors in a single, easy-to-pair large-format size and a coordinating mosaic.

DAVOS A

- REIMAGINING A CLASSIC
  - Small fossils and veining replicate the look of French limestone that has stood the test of time
  - Three rich neutral colors appeal to contemporary tastes 2CM thick tile available in 24 x 24 size
- AGELESS BEAUTY ANYWHERE
  - Random variations provide the ability to accommodate any outdoor design
  - Large-format size plus an available abstract mosaic provide dimensional depth

STONE

ΡΔ\/FF

EE CHARTS FOR FUL RODUCT DETAILS

## DIGNITARY™ COLORBODY<sup>™</sup> PORCELAIN PAVERS



## COLOR PALETTE



LUMINARY WHITE




NOTABLE BEIGE



SUPERIOR TAUPE









WATERPROOF







SCRATCH-RESISTANT FIRE-RESISTANT

SIMPLICLEAN™

SLIP RESISTANT

INDOOR/OUTDOOR

VISIT THE WHY TILE PAGE AT WWW.DALTILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.



NOTABLE BEIGE DR09



SUPERIOR TAUPE DR08

## DIGNITARY<sup>™</sup> COLORBODY<sup>™</sup> PORCELAIN PAVERS

## SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
24 x 24 Paver Tile	(23-3/8" x 23-3/8") (59.44 cm x 59.44 cm)	13/16" (2cm)	7.60	2

## **TRIM**<sup>†</sup>

	Туре	Notes
$\langle \rangle$	Rectified Step Nose	
	Coping	<ul> <li><sup>†</sup>Trim items available in many</li> </ul>
	Rectified Gutter	sizes and colors. Consult with your sales representative and/
	Rectified Grid	or design team for specifics.
	Rectified L-Kerb	

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	~
Wet & Level – Interior Floor	≥ 0.42	~
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	$\checkmark$
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	~
Countertops	N/A	~
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest<sup>™</sup>, visit daltile.com/DCOF.

## APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

## INSTALLATION

Dry Laying on Grass:	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
Dry Laying on Gravel:	Gaps of at least 3/16" (4 mm) should be left between slabs, using spacers to set the correct width. Joint may be left empty or filled with fine sand, polymeric sand specifically formulated for porcelain tile or small, clean aggregate, depending on the joint width and desired aesthetic.
Dry Laying on Sand:	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
Laying on Screed with Adhesive:	Slabs must be laid with open joints of variable width of no less than 3/16" (5 mm).
Raised Pavings:	Pedestal contains correct tile spacers for application.

## SHADE VARIATION

DR07, DR08, DR09

Random (V4) - Considerable Variation from Tile to Tile

## PERFORMANCE CHARACTERISTICS

ASTM#	Paver Result
C373	< 0.5%
C648	> 1000 lbs
MOHS	8.0
C650	Resistant
C1027	N/A
	C373 C648 MOHS

For additional information on test results, visit us at: daltile.com/information/TestResults.

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.







LEARN MORE

7834 C.F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.

