



FLOOR

EMBLEM™

GLAZED CERAMIC with REVEAL IMAGING®

 **daltile®**
IMAGINE WHAT'S POSSIBLE™



Above and cover photos feature Brown 7 x 20 field tile in a staggered brick-joint pattern on the floor.

Classic Richness
and Warmth of
Natural Wood
with Rugged
Durability

The classic look of rustic wood gives this tile a warm, inviting appearance with the richness found in nature. Now, with Emblem™ from Daltile, you can achieve the elegance of hardwood without compromise. Emblem mimics the look of natural wood, but in a ceramic tile that provides both beauty and outstanding durability.

- REVEAL IMAGING®
 - This proprietary imaging technology provides a realistic wood look, complete with knots and grain for an exact, elegant style
- EASY INSTALLATION & MAINTENANCE
 - Ceramic tile offers a more durable material for high traffic areas, with an ease of maintenance
- EXCELLENT VALUE
 - Get the natural look you desire at a price point that fits your budget



POST-CONSUMER
RECYCLED MATERIALS



PRE-CONSUMER
RECYCLED MATERIALS



REVEAL IMAGING®

FLOOR TILE



BEIGE EM 01



GRAY EM 03



BROWN EM 04

2 x 4 MOSAICS



BEIGE EM 01



GRAY EM 03





BROWN EM 04

EMBLEM™

GLAZED CERAMIC with REVEAL IMAGING®

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	7 x 20 Field Tile	(7-1/16" x 19-11/16") (18.00 cm x 50.00 cm)	5/16"	10.89	11
	2 x 4 Brick-joint Mosaic (Dot-mounted on 12"x12" Sheet)	(12"x12" Sheet) (30.48 cm x 30.48 cm Sheet)	1/4"	9.96	12

FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level- Interior	N/A	✓
Wet & Level- Interior	0.42	✓*
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	0.60	
Ramps & Inclines	0.65	

A DCOF value of 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest®, visit dalTile.com/DCOF.

OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	✓**


APPLICATION NOTES:

*Mosaics are suitable for residential and light commercial shower floors.

**Mosaic only


Suitable for exterior applications in non-freezing climates only when proper installation methods are followed.

TRIM

Type	Number	Size	Pieces per Carton
 Floor Bullnose	S-435K9	3-1/2 x 20	10

Floor bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (overlap should not exceed 33% when installing in a staggered brick-joint pattern) Mosaic: 1/8"	 High (V3)

TEST RESULTS

	ASTM #	Floor Result	Mosaic Result
Water Absorption	C373	< 70%	< 30%
Breaking Strength	C648	> 250 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant
Abrasion Resistance	C1027	4	4

For additional information, visit dalTile.com/information/TestResults.

NOTES

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to dalTile.com/LargeTiles form for more information.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at dalTile.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDITS. Form our detailed information, visit dalTilegreenworks.com.

SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GETDALTILE.COM



7834 C.F. Hawin Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at dalTile.com.



IMAGINE WHAT'S POSSIBLE™

© 2016 Dal-Tile Corporation (8/16)