



FLOOR

DIAMANTE™
COLORBODY™ PORCELAIN

 **daltile®**
IMAGINE WHAT'S POSSIBLE™

Close-up of
Field Tile



Cover and above photos feature Diamante™ Ardesia 18 x 18 in a grid pattern on the floor.

Rely on the Versatile Choice

Excellent colors and various sizes make this series a reliable choice for the distinguished office or retail space. Neutral beiges, taupes, and greys in smooth or stone-like looks round out a sensible palette. Six sizes, starting at 12 x 12 and going up to 24 x 24, offer a single solution for both an expansive or limited space.

- **COMMERCIAL GO-TO**

- A natural fit for distinguished commercial applications great for both expansive and limited spaces
- Available in six sizes both square and rectangular

- **FINISHES THAT IMPRESS**

- Smooth cement-look and varied stone-look graphics provide many options for creative design
- A Tru-Edge product that allows for narrower grout joints: 1/8 to 3/16



**PRE-CONSUMER
RECYCLED MATERIALS**



TRU-EDGE

All or select items within this series meet the requirements for these qualifications. For more product information, visit daltile.com.

**CERTIFIED
PORCELAIN
TILE**

© 2012 Daltile of North America, Inc.

FLOOR TILE SOPHISTICATO



ARDESTA P027 2



BIANCO P032 3



SABBIA P024 2



CREMA P022 2



GRIGIO P021 2



GHIACCIO P026 3



CORDA P033 3



TERRA P034 4

STOCKED COLORS & SIZES

Colors: P021, P022, P024, P027 and P032

Sizes: 12 x 12 Polished & Unpolished
12 x 24 Polished & Unpolished
4 x 12 Bullnose Polished & Unpolished
6 x 12 Cove Base
1 x 6 Cove Base Outcorner

PTS COLORS & SIZES





Colors: P026, P033 and P034

Sizes: All stocked field tile sizes
and 4 x 12 Bullnose Polished & Unpolished

FLOOR

DIAMANTE™

COLORBODY™ PORCELAIN

SIZES					
			Thickness	Sq.Ft. per Carton	Pieces per Carton
	24 x 24 FloorTile* (Polished & Unpolished)	(23-3/4" x 23-3/4") (60.30 cm x 60.30 cm)	5/16"	11.62	3
	12 x 24 FloorTile (Polished & Unpolished)	(11-11/16" x 23-3/4") (29.70 cm x 60.30 cm)	5/16"	11.62	6
	12 x 24 FloorTile (Polished & Unpolished) (P020 Only)	(11-3/4" x 23-15/16") (29.80 cm x 60.80 cm)	5/16"	15.49	8
	12 x 12 FloorTile (Polished & Unpolished)	(11-11/16" x 11-11/16") (29.70 cm x 29.70 cm)	5/16"	11.62	12
*Available as Special Order for P022, P024, P026, P027, P032 and P034 colors.					

FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level- Interior	N/A	✓
Wet & Level- Interior	0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	0.60	
Ramps & Inclines	0.65	




A DCOF value of 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	


Suitable for exterior applications in freezing and non-freezing climates only when proper installation methods are followed.
Polished surface is only suitable for dry and level floor applications.

TRIM

	Type	Number	Size	Pieces per Carton
	Bulnosc (Polished & Unpolished)	S-44C9	4 x 12	33 (Unpolished) 13 (Polished)
	Cove Base	S-36C9TB	6 x 12	8
	Cove Base Outcorner	SC-36C9TB	1 x 6	4

Bulnosc, cove base and cove base corner trim are intended to coordinate with floor tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern and/or when tile with a length 15" or greater is installed in a staggered brick-pint pattern. Overlap should not exceed 33%)	 Medium (V2)

TEST RESULTS

	ASTM #	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 515 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

NOTES

Manufacturer Advisory: Tiles with polished surface have a dynamic coefficient of friction < 0.42 as measured by the DCOF AcuTest method. Tiles with DCOF values < 0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at www.tileusa.com.
Special consideration must be given when installing tiles greater than 15 inches. Please refer to daltille.com/LargeTiles for more information.
Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Since there are variations in allied ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltille.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDENTIALS. For more detailed information, visit daltillegreenworks.com.



SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GETDALTILE.COM



7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltille® products and information, visit our website at daltille.com.



IMAGINE WHAT'S POSSIBLE™

© 2016 Daltille (11/16)