


SURETREAD SURFACE



Red 0Q 81 (1)



Wheat 0Q 79 (2)



Golden Brown 0Q 75 (2)



Bronze Clay 0Q 86 (2)



Gray 0Q 76 (2)



Storm Gray 0Q 82 (2)




Chocolate 0Q 88 (2)



Black 0Q 73 (2)

PAVER SURFACE



Red 0Q 84 (1)



Wheat 0Q 80 (2)



Golden Brown 0Q 78 (2)




Bronze Clay 0Q 87 (2)




Gray 0Q 85 (2)



Storm Gray 0Q 83 (2)



Chocolate 0Q 89 (2)



Black 0Q 74 (2)

(1) and (2) indicate price groups, (1) being the least expensive

Protect The Pep
In Your Step

• NATURAL RESISTANCE

- Available in a smooth paver surface and a textured tread surface
- Durable, natural product with low moisture absorption
- Textured surface provides excellent slip-resistance

• COMMERCIAL APPEAL

- Withstands extreme amounts of weight such as kitchen equipment and auto displays
- Tread surface prevents grease and water from building under feet
- Quarry Guard makes it easier to clean and stain-resistant



PRE-CONSUMER
RECYCLED MATERIALS




MADE IN THE U.S.A.

All or select items within this series meet the requirements for these qualifications. For more product information, visit daltile.com.

SURETREAD™ & PAVERS™

with QUARRY GUARD™

SIZES

			Thickness	Sq.Ft. per Carton	Pieces per Carton
	6 x 6 Floor Tile	(6" x 6") (15.20 cm x 15.20 cm)	3/8"	12.00	48

Sizing differences may exist between gray and red colors. When mixing colors, check actual samples to ensure sizing compatibility.

FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level- Interior	N/A	✓
Wet & Level- Interior	0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	0.60	✓
Subject to Oils	0.60	✓
Ramps & Inclines	0.65	

A DCOF value of 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	✓






APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

QUARRY GUARD™

QUARRY GUARD™ IMPROVES THE GROUT RELEASE AND STAIN RESISTANCE OF THE TILE, RESULTING IN EASIER CLEAN UP WITH INSTALLATION AND TILE THAT IS LESS LIKELY TO GET STAINED IN THE FUTURE.


TRIM

Type	Number	Size	Pieces per Carton
 Bullnose	P-1665	6 x 6	48
 Bullnose Corner	PC-1665	6 x 6	26
 Cove Base	P-3665	6 x 6	48
 Cove Base Corner	PCR-L-3665	6 x 6	26
 Cove Base Inside Corner	PB-3665	3/4 x 6	50

Bullnose, cove base, and cove base corner trim are intended to coordinate with floor tile in the standard 90-degree installation position.

Suretread trim is a smooth trim. Tread surface is not available on trim.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/8"	 Medium (V2)

TEST RESULTS

	ASTM #	Floor
Water Absorption	C373	3.0%
Breaking Strength	C648	> 400 lbs
Scratch Hardness	MOHS	70
Chemical Resistance	C650	Resistant

NOTES

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltile.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltilegreenworks.com.

SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GETDALITTLE.COM



7834 C.F. Hawin Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.

