

FLOOR TILE



RED BLAZE OQ40 (1)



BLAZE FLASH OQ41 (2)



ARID GRAY OQ42 (2)



ARID FLASH OQ48 (2)

Texture Notes:

(1) and (2) indicate price groups, (1) being the least expensive.
All colors are available in abrasive surface 6 x 6.
Only OQ40 and OQ41 are available in abrasive surface in 4 x 8.
Double abrasive available on floor tile in all colors on a special order basis.





**PRE-CONSUMER
RECYCLED MATERIALS**



MADE IN THE U.S.A.

All or select items within this series meet the requirements for these qualifications. For more product information, visit daltile.com.

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	6 x 6 Floor Tile	(6" x 6") (15.20 cm x 15.20 cm)	1/2"	11.00	44
	4 x 8 Floor Tile*	(4" x 8") (10.20 cm x 20.30 cm)	1/2"	10.76	50

* Available in Red Blaze OQ40 and Red Blaze Flash OQ41 only.

FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	✓
Subject to Oils	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	✓*

A DCOF value of ≥ 0.42 is the standard for tiles for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	✓



APPLICATION NOTES:

* Abrasive surface only









Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

Suitable for industrial installation requiring high compressive strength.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/8"	 High (V3) - non-Flash colors  Random (V4) - Flash colors

TRIM

	Type	Number	Size	Pieces per Carton
	Bullnose	Q-1485*†	4 x 8	50
	Bullnose Corner	QCR-L-1485*†	4 x 8	20
	Bullnose	Q-1665*	6 x 6	44
	Bullnose Corner	QCRL-1665*	6 x 6	44
	Cove Base	Q-3565*	5 x 6	44
	Cove Base Corner	QCR-L-3565**	5 x 6	20
	Cove Base Inside Corner	QB-3565*	1 x 5	25
	Cove Base Outside Corner	QC-3565*	1 x 5	20

Bullnose, cove base and cove base corner trim are intended to coordinate with floor tile in the standard 90-degree installation position.

* Available in abrasive grain.

† Available in colors OQ40 and OQ41 only.

• Not available with abrasive surface or in Flash colors; use coordinating solid.

▪ Made-to-order

TEST RESULTS

	ASTM#	Result
Water Absorption	C373	< 3.0%
Breaking Strength	C648	> 350 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant

NOTES

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Abrasive surface suitable for use on ramps.

For additional information refer to "Factors to Consider" at daltile.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltilegreenworks.com.

SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GET.DALTILE.COM



7834 C. F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.

