


FLOOR TILE



BIANCO
GHIACCIO-SOLID
CD28 (2)



FUORI DI
BIANCO CD39 (1)



BEIGE CD31 (1)



BIANCO
ALPI CD05 (1)



PEPE GRIGIO CD41 (1)



GRIGIO
GRANITE CD40 (1)



MANDORLA CON
SPEZIA CD78 (1)



MARRONE
CANNELLA CD77 (1)



ROSA
ANTICO CD56 (1)



LABRADORITE
CD49 (1)



VERDE
ALGHERO CD07 (1)



GRIGIO
SCURO CD42 (1)



NERO
MACCHIATO CD37 (1)

Powerful Performance with the Look of Luxury

Nothing is more inspiring than running warm sand through your fingers; this was the inspiration behind the Porcealto collection. Serenely beautiful, you would never guess that this organic beauty can withstand the toughest stains and even frost. Available in a range of colors and surface finishes, Porcealto never fails to provide an added depth to your space.



- STRONG DESIGN
 - Organic design inspired by warm sand
 - Technical ColorBody™ porcelain for commercial applications
- BEAUTIFUL FINISH
 - Available in polished, unpolished and textured surfaces
 - Coordinating trim available for those finishing touches


**PRE-CONSUMER
RECYCLED MATERIALS**



All or select items within this series meet the requirements for these qualifications. For more product information, visit daltile.com.



SIZES (See charts below for sizes & surfaces available by color)

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	12 x 12 Floor Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	15.00	15
	8 x 8 Floor Tile	(7-13/16" x 7-13/16") (19.80 cm x 19.80 cm)	5/16"	13.30	30

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/4"	 Medium (V2)  Low (V1) - CD28

FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓*
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	✓**
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	

APPLICATION NOTES:

* Unpolished and Textured only

** Textured only

Suitable for exterior applications in freezing and nonfreezing climates, when proper installation methods are followed.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

TEST RESULTS

	ASTM#	Unpolished Result	Textured Result	Polished Result
Water Absorption	C373	< 0.5%	< 0.5%	< 0.5%
Breaking Strength	C648	478 lbs	520 lbs	497 lbs
Scratch Hardness	MOHS	7.5	8.0	7.5
Chemical Resistance	C650	Resistant	Resistant	Resistant

CD28 - Trim

	S-36C9T 6 x 12 CV BS	SC-36C9T 1 x 6 CV Out	S-44C9 4 x 12 SBN
CD28	STK	STK	STK

Floor bullnose and cove base trim are intended to coordinate with floor tile in the standard 90-degree installation position.

FLOOR TILE

	8 x 8 Unpolished	8 x 8 Textured	12 x 12 Unpolished	12 x 12 Polished	12 x 12 Textured
CD05	STK	SP	STK	STK	STK
CD07	STK	N/A	STK	SP	N/A
CD31	STK	SP	STK	STK	STK
CD37	STK	N/A	STK	STK	N/A
CD39	STK	N/A	STK	STK	N/A
CD40	STK	N/A	STK	STK	STK
CD41	STK	SP	STK	STK	STK
CD42	STK	SP	STK	STK	SP
CD49	STK	N/A	STK	SP	N/A
CD56	STK	N/A	STK	STK	N/A
CD77	STK	N/A	STK	STK	N/A
CD78	STK	N/A	STK	STK	N/A

FLOOR TILE TRIM

	S-4489 4 x 8 SBN	S-3689T 6 x 8 CV Base	SB-3689T 1 x 6 CV In	SC-3689T 1 x 6 CV Out	S-44C9 4 x 12 SBN	12 x 12 Stair Tread
CD05	STK	STK	STK	STK	STK	SP
CD07	STK	STK	STK	STK	STK	SP
CD31	STK	STK	STK	STK	STK	SP
CD37	STK	STK	STK	STK	STK	N/A
CD39	STK	STK	STK	STK	STK	SP
CD40	STK	STK	STK	STK	STK	SP
CD41	STK	STK	STK	STK	STK	SP
CD42	STK	STK	STK	STK	STK	SP
CD49	STK	STK	STK	STK	STK	SP
CD56	STK	STK	STK	STK	STK	SP
CD77	STK	STK	STK	STK	STK	N/A
CD78	STK	STK	STK	STK	STK	N/A

Floor bullnose, cove base, and cove base corner trim are intended to coordinate with floor tile in the standard 90-degree installation position.

STK - Stocked SP - Special Order N/A - Not Available



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltilegreenworks.com.

7834 C. F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2017 Daltile (4/17)