



FLOOR

TIMBER GLEN™
COLORBODY™ PORCELAIN

 **daltile®**
IMAGINE WHAT'S POSSIBLE™




Photo features Timber Glen™ Cocoa 6 x 24 in a staggered brick-joint pattern on the floor.

Contemporary Spin on Rustic Hardwood

Timber Glen provides the character of wood-look with a modern twist. This stylized hand-scraped look captures the rich essence of wood planking in five exquisite natural tones. With its contemporary character and natural elegance, Timber Glen offers a discriminating fashion sense to any room.

- MODERN TAKE ON A POPULAR DESIGN
 - Modern, stylized take on traditional wood-looks
 - hand-scraped look adds contemporary styling
- NATURAL DESIGN
 - Six lush nature-inspired tones add warmth and richness to space
 - Size and graphic presents an authentic wood look

 PRE-CONSUMER
RECYCLED MATERIALS

 TRU-EDGE

All or select items within this series meet the requirements for these qualifications. For more product information, visit daltile.com

 CERTIFIED
DALTILE
PROFESSIONAL
TILE SOLUTIONS

Professional
TILE SOLUTIONS

FLOOR TILE



THATCH P625



DUNE P620



HICKORY P621



COCOA P623



CHERRY P622





ESPRESSO P624

TIMBER GLEN™

COLORBODY™ PORCELAIN

SIZES

			Thickness	Sq.Ft. per Carton	Pieces per Carton
	12 x 24 Floor Tile	(11-13/16" x 23-5/8") (30.00 cm x 60.00 cm)	3/8"	1162	6
	6 x 24 Floor Tile	(5-7/8" x 23-5/8") (15.00 cm x 60.00 cm)	3/8"	1162	12

FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level- Interior	N/A	✓
Wet & Level- Interior	0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	0.60	
Ramps & Inclines	0.65	

A DCOF value of 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSIA 1371-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.


OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	

APPLICATION NOTES:


Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

TRIM

Type	Number	Size	Pieces per Carton
 Bullnose	S-44F9	4 x 24	16

Bullnose trim is intended to coordinate with floor tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern and/or when tile with a length 15" or greater is installed in a staggered brick-joint pattern. Overlap should not exceed 33%)	 Medium (V2)

TEST RESULTS

	ASTM #	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 450 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

NOTES

Special consideration must be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSIA 1371 standards.

Water, oil, grease, etc. create slippery conditions. For applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltile.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDITS. Form our detailed information, visit daltilegreenworks.com.

SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GETDALITILE.COM



7834 C.F. Hawin Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

© 2016 Daltile (11/16)