



FLOOR | WALL

PARKWAY™

GLAZED CERAMIC with REVEAL IMAGING®

 **daltile®**
IMAGINE WHAT'S POSSIBLE™



Cover photo features Gray 12 x 24 field tile in a grid pattern on the floor.
Above photo features Beige 12 x 24 field tile in a grid pattern on the floor.

The Sleek Look of Concrete

Bring the trendy, modern-day look of stained concrete into your space. Perfect for the coffee house downtown, your home, loft or beyond, the look of stained concrete and cement creates a sleek and cozy feel in any space. This series is easily customizable with both floor and wall sizes, and a contemporary color palette. Simple to maintain and very durable, Parkway™ gives your space a modern feel.

- MODERN VERSATILE DESIGN
 - Fresh design mimics the look of concrete and cement
 - Choose from a color palette that seamlessly blends with any space
- UNIQUE OPTIONS
 - Featuring larger sizes to create the most stylish look
 - Complementary floor and wall tile to finish any space



POST-CONSUMER RECYCLED MATERIALS



PRE-CONSUMER RECYCLED MATERIALS



MADE IN THE U.S.A.



REVEAL IMAGING®

All or select items within this series are made in the USA. For more information, visit daltile.com/Parkway.

FIELD TILE



BEIGE PK96



CREAM PK95



BROWN PK97



GRAY PK98

WALL TILE



CREAM PK95



BEIGE PK96



BROWN PK97



GRAY PK98

PARKWAY™

GLAZED CERAMIC with REVEAL IMAGING®








SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	18 x 18 Floor Tile*	(17-1/2" x 17-1/2") (44.45 cm x 44.45 cm)	5/16"	17.04	8
	12 x 12 Floor Tile*	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	14.55	15
	12 x 24 Floor Tile	(11-9/16" x 23-3/8") (29.40 cm x 59.30 cm)	3/8"	15.04	8
	9 x 12 Wall Tile	(9" x 12") (22.91 cm x 30.54 cm)	5/16"	11.25	15
	6 x 6 Wall Tile	(6" x 6") (15.20 cm x 15.20 cm)	5/16"	12.50	50

* This product is manufactured regionally. Slight variances in size and shading may occur between regions. Please contact your sales representative to verify carton square footage. As with all tile projects, be sure to purchase sufficient quantities with your initial order.

Floor tile sizes are not intended to be modular.

TRIM

	Type	Number	Size	Pieces per Carton
	Floor Bullnose*	S-43C9	3 x 12	20
	Wall Bullnose	S-4669	6 x 6	50
	Wall Bullnose Corner	SCRL-4669	6 x 6	50
	Wall Bullnose	S-4309	3 x 9	54
	Wall Bullnose Corner	SN-4309	3 x 3	32
	Quarter Round	A106	1 x 6	152
	Quarter Round Corner	UC106	1 x 1	40

*Floor bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

INSTALLATION

Thickness	Grout Joint Recommendation	Shade Variation
Wall : 5/16" Floor : 12 x 12 & 18 x 18 : 5/16", 12 x 24 : 3/8"	Floor: 3/16" Wall: 1/16"	 Medium (V2)

FLOOR APPLICATIONS

(Excludes Wall Tile)	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓*
Pool Linings	✓**

APPLICATION NOTES:

* 9 x 12 wall tile not suitable for countertops

** 6 x 6 wall tile only

Suitable for exterior applications in non-freezing climates only when proper installation methods are followed.

TEST RESULTS

	ASTM#	Floor Result	Wall Result
Water Absorption	C373	< 7.0%	< 20.0%
Breaking Strength	C648	> 250 lbs.	120-230 lbs.
Scratch Hardness	MOHS	7.0	4.0-6.0
Chemical Resistance	C650	Resistant	Resistant
Abrasion Resistance	C1027	3	N/A

For additional information, visit daltille.com/information/TestResults.

NOTES

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltille.com/LargeTiles for more information.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A1371 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltille.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltillegreenworks.com.



SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GET.DALTILE.COM



7834 C. F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltille® products and information, visit our website at daltille.com.



IMAGINE WHAT'S POSSIBLE™

©2016 Dal-Tile Corporation (6/16)