



WALL

IDYLLIC BLENDS™
GLASS, STONE & LVT MOSAIC

 **daltile®**
IMAGINE WHAT'S POSSIBLE™



Cover and above photos feature Idyllic Blends™ Tranquil Snow 2" hexagon mosaic on the backsplash.

The Striking Look of Cubism

Be inspired by the intriguing geometric shapes of Idyllic Blends™. Influenced by cubic art, linear and hexagonal mosaics are pieced together randomly for a visually captivating appearance. Idyllic Blends was designed to stand out, making it perfect for walls and backsplashes. The collection playfully brings together cool undertones and warm shades.

- **OUTSTANDING DESIGN**
 - Captivating stone and wood visuals
 - Unique combination of cool and warm shades
- **ARTISTIC APPROACH**
 - Color and gradient variation for an unexpected, exciting design
 - Random linear and 2-inch hexagon mosaics
 - Available in four mixed-shade color blends

USAGE

Floors

Walls

Countertops



W



IDYLLIC BLENDS™

GLASS, STONE & LVT MOSAIC

2" HEXAGON MOSAIC



TRANQUIL SNOW IB01



SERENE STORM IB04



SYLVAN SUNSET IB02



RUSTIC EVE IB03

RANDOM LINEAR MOSAIC



TRANQUIL SNOW IB01



SERENE STORM IB04



SYLVAN SUNSET IB02



RUSTIC EVE IB03

IDYLLIC BLENDS™

GLASS, STONE & LVT MOSAIC

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
	2" Hexagon Mosaic (Mesh-mounted)	(10-7/8" x 11-1/16" Sheet) (27.60 cm x 28.09 cm Sheet)	3/16"	11.40 15
	Random Linear Mosaic (Mesh-mounted)	(13-7/8" x 11-9/16" Sheet) (35.22 cm x 71.34 cm Sheet)	3/16"	14.40 15

APPLICATIONS


	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Mosaics suitable for interior applications only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" Approximately	 Random (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 100 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Non-Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.2 standards.

Use of a white latex modified thin-set is recommended for installation.



DESIGNED TO HELP EARN LEED™
CREDITS. For more detailed information,
visit daltilegreenworks.com.



SCAN QR CODE
FOR PRODUCT
INFORMATION

Get a QR Code
reader at:
GET.DALTILE.COM



7834 C. F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2017 Daltile (4/17)