



WALL

**RETROSPACE™**  
GLAZED CERAMIC

 **daltile®**  
IMAGINE WHAT'S POSSIBLE™



Cover and above photos feature RetroSpace™ Modern White 3 x 6 wall tile and 3 x 6 diamond accent on the backsplash with Natural Quartzite Tahitian Cream on the countertops.

## Mid-Century Modern Essentials

Reinvent the acclaimed look of mid-century modern design with RetroSpace™. A modern interpretation of a nostalgic aesthetic, this translucent-glazed wall tile beautifully reflects light in your space. A subtle undulated surface is the foundation of this artisan wall tile available in soft green and blue hues as well as a neutral color palette. RetroSpace is offered in three wall tile sizes and two decorative geometric designs which can be combined to create one-of-a-kind feature walls or backsplashes.

- **SOFT REFLECTIONS**
  - Subtle, minimalistic wall tile with an enriching, translucent glaze
  - Combine shapes and colors to create unique, personalized wall designs
- **DIMENSIONAL SURFACE**
  - Diamond and Wave accents available in 3 x 6 wall tile
  - Soft green and blue tones offered along with traditional neutral colors
  - Three wall tile sizes with coordinating chair rail and jolly

### USAGE

Floors

Walls

Countertops



W



### 3 x 6 WALL TILE



MODERN  
WHITE RS30



MERCURY  
GREY RS31



SYCAMORE  
TAN RS32



SUCCULENT  
GREEN RS34



SKY  
BLUE RS33




JET  
BLACK RS35

### 6 x 6 WALL TILE



MODERN  
WHITE RS30



MERCURY  
GREY RS31



SYCAMORE  
TAN RS32



SUCCULENT  
GREEN RS34



SKY  
BLUE RS33




JET  
BLACK RS35

### 6 x 6 HEXAGON WALL TILE




MODERN  
WHITE RS30



MERCURY  
GREY RS31




SYCAMORE  
TAN RS32



SUCCULENT  
GREEN RS34



SKY  
BLUE RS33



JET  
BLACK RS35




Photo features RetroSpace™ Modern White 3 x 6 and 6 x 6 and Succulent Green 6 x 6 on the wall.

WALL

# RETROSPACE™

GLAZED CERAMIC

## 3 x 6 WAVE ACCENT



MODERN WHITE RS30



MERCURY GREY RS31



SYCAMORE TAN RS32



SUCCULENT GREEN RS34




SKY BLUE RS33



JET BLACK RS35

## 3 x 6 DIAMOND ACCENT



MODERN WHITE RS30



MERCURY GREY RS31



SYCAMORE TAN RS32



SUCCULENT GREEN RS34




SKY BLUE RS33



JET BLACK RS35


## 1/2 x 12 JOLLY




MODERN WHITE RS30



MERCURY GREY RS31



SYCAMORE TAN RS32



SUCCULENT GREEN RS34



SKY BLUE RS33



JET BLACK RS35

## 1 x 6 CHAIR RAIL



MODERN WHITE RS30



MERCURY GREY RS31



SYCAMORE TAN RS32



SUCCULENT GREEN RS34



SKY BLUE RS33



JET BLACK RS35

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	6 x 6 Wall Tile	(5-7/8" x 5-7/8") (15.00 cm x 15.00 cm)	1/4"	11.52	48
	6 x 6 Hexagon Wall Tile	(5-7/8" x 5-7/8") (15.00 cm x 15.00 cm)	1/4"	11.04	48
	3 x 6 Wall Tile	(2-15/16" x 5-7/8") (7.40 cm x 15.00 cm)	1/4"	11.52	96
	3 x 6 Wave Accent	(2-15/16" x 5-7/8") (7.40 cm x 15.00 cm)	5/16"	N/A	88
	3 x 6 Diamond Accent	(2-15/16" x 5-7/8") (7.40 cm x 15.00 cm)	5/16"	N/A	88

## APPLICATIONS



	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).


### APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

## TRIM

	Type	Number	Size	Pieces/ Carton
	Chair Rail	16CR	1 x 6	40
	12" Jolly	S1/212J	1/2 x 12	12

## INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8"	 Low (V1)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120-230 lbs
Scratch Hardness	MOHS	4.0-6.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).



DESIGNED TO HELP EARN LEED™  
 CREDITS. For more detailed information,  
 visit [daltilegreenworks.com](http://daltilegreenworks.com).

7834 C.F. Hawn Freeway,  
 Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of  
 Daltile® products and information,  
 visit our website at [daltile.com](http://daltile.com).



IMAGINE WHAT'S POSSIBLE™

©2017 Daltile (10/17)