

FLOOR

GLEN ARBOR™

GLAZED CERAMIC

 **daltile**[®]
IMAGINE WHAT'S POSSIBLE™

FLOOR TILE



NATURAL GA01



BROWN GA02



GREY GA03



**PRE-CONSUMER
RECYCLED MATERIALS**



REVEAL IMAGING®


All or select items within this series meet the requirements for these qualifications. For more product information, visit daltile.com.

 **daltile**[®]

IMAGINE WHAT'S POSSIBLE™

©2018 Daltile (1/18)

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	6 x 26 Floor Tile	(6-1/8" x 26-1/8") (15.60 cm x 66.40 cm)	3/8"	16.65	15

APPLICATIONS


	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	 High (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 7.0%
Breaking Strength	C648	> 250 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	3

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.



DESIGNED TO HELP EARN LEED™
 CREDITS. For more detailed information,
 visit daltilegreenworks.com.

7834 C. F. Hawn Freeway,
 Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
 Daltile® products and information,
 visit our website at daltile.com.



©2018 Daltile (1/18)