



MOSAIC

COLOR WHEEL™ MOSAICS  
GLAZED CERAMIC



 daltile®  
IMAGINE WHAT'S POSSIBLE™

# COLOR WHEEL™ MOSAICS

GLAZED CERAMIC

## A Spectacular Spectrum

The element of color is visually represented in Color Wheel™. This vibrant collection offers a wide spectrum of colorful selections from bright and pigmented hues to neutral and earthy tones. A favorite of artists and designers, Color Wheel provides the perfect palette to inspire the imagination.

### • COLOR SCHEME

- Eight rich semi-gloss colorful accents
- Plus, eight coordinating neutral tones in semi-gloss and matte finishes

### • ARTISTIC INSPIRATIONS

- Stylish shapes from unique linear sizes to exciting mosaic designs
- With endless design opportunities, this collection is a perfect fit for residential and commercial applications



Cover photo features Color Wheel™ Mosaics Matte Arctic White 1 x 6 mosaic on the wall, Ocean Blue & Matte Arctic White 1.5" Hexagon mosaic on the right wall, Matte Arctic White Penny Round mosaic on the shower floor and Gamma™ Hypnotic 12 x 24 matte on the floor.

Above photo features Color Wheel™ Mosaics Mustard, Orange Burst, Currant & Arctic White Penny Round mosaics on the fountain and Keystones™ Matte Arctic White 2 x 2 mosaic in the pool.

### MOSAIC

### USAGE



### SPECIAL FEATURES

SEE CHARTS FOR FULL PRODUCT DETAILS

SIZES:



2 x 2 Mosaic



1.5" Hexagon Mosaic



1.5" Arctic White & Black Hexagon Mosaic\*



1 x 6 Mosaic



1 x 3 Herringbone Mosaic




1 x 3 Lattice Weave Mosaic



Penny Round Mosaic

FINISHES: SEMI-GLOSS | MATTE

SEMI-GLOSS



BLACK K111 (2)



ARCTIC WHITE 0190 (1)



BISCUIT K175 (1)



URBAN PUTTY 0161 (2)



ARCHITECTURAL GRAY 0109 (2)




DESERT GRAY X114 (1)



SUEDE GRAY 0182 (2)



CHALKBOARD 0180 (2)



ARCTIC WHITE WITH BLACK PENNY ROUND MOSAIC CW50 GLOSS

MATTE



MATTE BLACK K711 (2)



MATTE ARCTIC WHITE 0790 (1)



MATTE BISCUIT K775 (1)



MATTE URBAN PUTTY 0761 (2)



MATTE ARCHITECTURAL GRAY 0709 (2)




MATTE DESERT GRAY X714 (1)



MATTE SUEDE GRAY 0782 (2)



MATTE CHALKBOARD 0780 (2)



MATTE ARCTIC WHITE WITH MATTE BLACK PENNY ROUND MOSAIC CW51 MATTE


ACCENT+



MUSTARD 1012 (3)



ORANGE BURST 1097 (3)



CURRENT SH17 (3)



EMERALD 0115 (3)



SEA BREEZE 1174 (3)



OCEAN BLUE 1049 (3)




NAVY K189 (3)



PLUM CRAZY 1178 (3)

SIZES




2 x 2 MOSAIC (DOT-MOUNTED ON 12" x 24" SHEET)




1 x 6 MOSAIC (DOT-MOUNTED ON 10" x 12" SHEET)



1.5" HEXAGON MOSAIC (DOT-MOUNTED ON 12" x 11" SHEET)



1 x 3 HERRINGBONE MOSAIC (DOT-MOUNTED ON 9" x 12" SHEET)



1.5" ARCTIC WHITE WITH BLACK HEXAGON MOSAIC\* CW50 GLOSS AND CW51 MATTE (MESH-MOUNTED ON 14" x 12" SHEET)



PENNY ROUND MOSAIC\* (DOT-MOUNTED ON 13" x 13" SHEET)



1 x 3 LATTICE WEAVE MOSAIC (DOT-MOUNTED ON 12 x 12 SHEET)

+ Accent available in Semi-Gloss finish only.

(1), (2) and (3) indicate price groups. (1) being the least expensive.

Shapes stocked in all colors. Blends and patterns are also available on a made to order basis.

\* Stocked in all colors and patterns (CW50 Gloss and CW51 Matte).

Other pattern and blend options available (in any size, color or finish) on a made to order basis.



SLIP RESISTANT



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT\*  
\*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT™  
™Not Applicable to Mesh-Mounted Mosaics



CLIMATEPRO™



SIMPLICLEAN™

# COLOR WHEEL™ MOSAICS

GLAZED CERAMIC

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	2 x 2 Mosaic (Dot-mounted on 12" x 24" Sheet)	(12" x 24" Sheet) (30.48 cm x 60.96 cm Sheet)	1/4" (6 mm)	24.00	12
	1 x 6 Mosaic (Dot-mounted)	(9-3/4" x 11-1/2" Sheet) (24.76 cm x 29.21 cm Sheet)	5/16" (8 mm)	8.30	10
	1.5" Hexagon Mosaic (Dot-mounted on 12" x 11" Sheet)	(11-5/8" x 10-1/4" Sheet) (28.89 cm x 26.04 cm Sheet)	1/4" (6 mm)	9.72	12
	1.5" White & Black Hexagon Mosaic (Mesh-mounted on 14" x 12" Sheet)	(14" x 11-1/2" Sheet) (35.56 cm x 29.21 cm Sheet)	1/4" (6 mm)	10.00	10
	1 x 3 Herringbone Mosaic (Dot-mounted)	(9" x 12" Sheet) (22.86 cm x 30.48 cm Sheet)	1/4" (6 mm)	6.00	10
	3/4" Penny Round Mosaic (Dot-mounted)	(11-3/8" x 13-3/8" Sheet) (28.89 cm x 33.97 cm Sheet)	1/4" (6 mm)	10.60	10
	1 x 3 Lattice Weave Mosaic (Dot-mounted)	(12" x 12" Sheet) (30.48 cm x 30.48 cm Sheet)	1/4" (6 mm)	10.00	10

\* Stocked in Arctic White with Black (both CW50 gloss and CW51 matte).  
Other pattern options available on a made to order basis.

♦ Penny Round mosaics are stocked in all colors and in  
CW50 Gloss & CW51 Matte Arctic White with Black patterns.

## LRV & MUNSELL

Color #	LRV Illuminate-OBS: F02-02 (CWF)	Munsell
<b>SEMI-GLOSS</b>		
0190	83.9	7.0Y 9.2/0.2
K175	75.9	5.2Y 8.8/0.9
0161	48.0	1.7Y 7.3/1.5
0109	37.9	6.0Y 6.6/1.0
X114	43.7	1.4GY 7.0/0.3
0182	22.6	1.9B 5.3/0.1
0180	11.4	1.3B 3.9/0.4
K111	5.0	10.0B 2.6/0.1
<b>MATTE</b>		
0790	83.4	4.9Y 9.2/0.2
K775	75.9	5.2Y 8.8/0.9
0761	48.1	2.5Y 7.3/1.5
0709	36.9	5.6Y 6.5/1.0
X714	43.9	3.6GY 7.0/0.4
0782	22.3	9.8G 5.3/0.1
0780	11.1	0.6B 3.9/0.4
K711	5.8	3.3PB 2.8/0.1
<b>ACCENT</b>		
K189	5.9	5.0PB 2.9/1.2
1012	48.1	9.7YR 7.2/6.9
1049	18.0	1.9B 5.0/4.5
1097	26.4	10.1R 5.6/10.2
0115	12.4	3.4G 4.2/4.6
1174	9.1	5.8PB 3.6/5.6
1178	6.8	5.9RP 3.1/2.0
SH17	14.0	5.1R 4.4/11.1

## TRIM

Type	Number	Size	Pieces/ Carton
 12" Jolly	S-1/212J	1/2 x 11-15/16	12

Jolly suitable for wall applications only.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
Mosaic: 1/8"	 Low (V1)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Gloss Result	Matte Result
Water Absorption	C373	< 3.0%	< 3.0%
Breaking Strength	C648	> 250 lbs	> 250 lbs
Scratch Hardness	MOHS	4.0-6.0	8.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at:  
[daltille.com/information/TestResults](http://daltille.com/information/TestResults).

## NOTES

Since there are variations in all fired ceramic and natural products,  
tile and trim supplied for your particular installation may not match  
samples. Final confirmation should be made from actual tiles and  
trim prior to installation. Manufactured in accordance with ANSI A137.1  
standards.

Not for use on ramps. Water, oil, grease, improper drainage and  
certain footwear can create slippery conditions. Floor applications  
expected to be exposed to these conditions require extra caution in  
product selection.

For additional information refer to "Factors to Consider" at:  
[daltille.com/Factors](http://daltille.com/Factors).

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓*
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors (Residential or Commercial)	≥ 0.42	✓*
Exterior Floor Applications, including Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

\* Matte Mosaics Only

† Darker colors may show scratches

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	④ All Residential / Commercial

Note: Matte colors only.



POST-CONSUMER RECYCLED MATERIALS



PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit [daltile.com](http://daltile.com).