



FLOOR

**MEMOIR™**  
GLAZED CERAMIC

 **daltile®**  
IMAGINE WHAT'S POSSIBLE™





Cover photo features Memoir™ Petal Black 12 x 12 on the floor with Panoramic Porcelain Surfaces™ Manor White on the countertop. Above photo features Memoir™ Star Grey 12 x 12 on the fireplace.

## Historic Design

Catch a glimpse of historic design with Memoir™. This mesmerizing assortment consists of concrete-like encaustic tile in two patterns and two contemporary colors. Memoir™ is a collection that will make a statement and create everlasting memories.

- MEMORABLE DESIGNS
  - Two traditional encaustic patterns in geometrical and floral designs, which create a continuous pattern from piece to piece
  - Offered in two contemporary colors, Offered in two contemporary color ways
- DESIGN WITH CHARACTER
  - 12 x 12 size suitable for both floor and wall applications
  - Can be utilized as stand-alone or paired as a decorative accent with other collections like Koncrete™
  - Made in the USA with Reveal Imaging™ Technology

 **PRE-CONSUMER RECYCLED MATERIALS**

 **MADE IN THE U.S.A.**

 **REVEAL IMAGING®**

All or select items within this series meet the requirements for these qualifications. For more information visit [datile.com](http://datile.com).

### USAGE

Floors Walls Countertops

F W C



GLAZED CERAMIC FLOOR TILE



PETAL GREY ME20



PETAL BLACK ME21



STAR GREIGE ME22




STAR GREIGE ME23

# MEMOIR™

GLAZED CERAMIC

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	12 x 12 Floor Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	15.52	16

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [daltille.com/DCOF](http://daltille.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16"	 Medium (V2)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 7.0%
Breaking Strength	C648	> 250 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	3

For additional information on test results, visit us at: [daltille.com/information/TestResults](http://daltille.com/information/TestResults).

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A1371 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [daltille.com/Factors](http://daltille.com/Factors).



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit [daltillegreenworks.com](http://daltillegreenworks.com).

7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltille® products and information, visit our website at [daltille.com](http://daltille.com).



©2019 Daltille (1/19)