



WALL

# LINEAR

COLOR WHEEL™ COLLECTION – GLAZED CERAMIC

 **daltile**<sup>®</sup>  
IMAGINE WHAT'S POSSIBLE™



Cover photo features Color Wheel™ Linear Arctic White, Desert Gray & Chalkboard 6 x 18 on wall.  
 Above photo features Color Wheel™ Linear Arctic White & Plum Crazy 6 x 18 on wall.

## A Spectacular Spectrum

The element of color is visually represented in Color Wheel™. This vibrant collection offers a wide spectrum of colorful selections from bright and pigmented hues to neutral and earthy tones. A favorite of artists and designers, Color Wheel provides the perfect palette to inspire the imagination.

- COLOR SCHEME
  - Eight rich semi-gloss colorful accents
  - Plus, eight coordinating neutral tones in semi-gloss and matte finishes
- ARTISTIC INSPIRATIONS
  - Stylish shapes in unique linear sizes
  - With endless design opportunities, this collection is a perfect fit for residential and commercial applications



**POST-CONSUMER RECYCLED MATERIALS**



**PRE-CONSUMER RECYCLED MATERIALS**

All or select items within this series meet the requirements for these qualifications. For more information visit [daltile.com](http://daltile.com).

### USAGE

Floors

Walls

Countertops



W




# LINEAR

COLOR WHEEL™ COLLECTION – GLAZED CERAMIC

## SEMI-GLOSS



BLACK  
K111 (2)




ARCTIC WHITE  
O190 (1)



BISCUIT  
K175 (1)




URBAN PUTTY  
O161 (2)




ARCHITECTURAL  
GRAY O109 (2)



DESERT GRAY  
X114 (1)



SUEDE GRAY  
O182 (2)




CHALKBOARD  
O180 (2)


## MATTE




MATTE BLACK  
K711 (2)



MATTE ARCTIC WHITE  
O790 (1)



MATTE BISCUIT  
K775 (1)



MATTE URBAN PUTTY  
O761 (2)



MATTE ARCHITECTURAL  
GRAY O709 (2)



MATTE DESERT GRAY  
X714 (1)



MATTE SUEDE GRAY  
O782 (2)



MATTE CHALKBOARD  
O780 (2)

## ACCENT\*



MUSTARD  
1012 (3)



ORANGE BURST  
1097 (3)



CURRANT  
SH17 (3)



EMERALD  
O115 (3)



SEA BREEZE  
1174 (3)



OCEAN BLUE  
1049 (3)



NAVY  
K189 (3)



PLUM CRAZY  
1178 (3)







\*Accent available in Semi-Gloss finish only.

(1), (2) and (3) indicate price groups. (1) being the least expensive.

# LINEAR

COLOR WHEEL™ COLLECTION – GLAZED CERAMIC

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	8 x 24 Wall Tile	(8" x 24") (20.34 cm x 61.03 cm)	3/8" (9.3 mm)	13.30	10
	6 x 18 Wall Tile	(6" x 18") (15.25 cm x 45.76 cm)	3/8" (9.3 mm)	11.25	15
	4 x 16 Wall Tile	(4" x 16") (10.17 cm x 40.68 cm)	3/8" (9.3 mm)	13.20	30
	4 x 12 Wall Tile	(4-1/4" x 12-7/8") (10.91 cm x 32.77 cm)	5/16" (7.9 mm)	10.64	28
	4 x 8 Wall Tile	(4-1/4" x 8-9/16") (10.91 cm x 21.82 cm)	5/16" (7.9 mm)	10.63	42
	2 x 8 Wall Tile	(2-1/8" x 8-9/16") (5.45 cm x 21.82 cm)	5/16" (7.9 mm)	10.40	80

## APPLICATIONS










	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).


### APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

## TRIM

	Type	Number	Size	Pieces/ Carton
	Jolly	S-1/212J	1/2 x 11-15/16	12
	Wall Bullnose	S-44D9	4 x 16	24
	Wall Bullnose Corner	SN-44D9	4 x 4	20
	Wall Bullnose	S-44C9MOD	4-1/4 x 12-7/8	28
	Wall Bullnose	S-4489MOD	4-1/4 x 8-9/16	42
	Wall Bullnose Corner	SCRL-4449	4-1/4 x 4-1/4	100
	Wall Bullnose	S-4289MOD	2-1/8 x 8-9/16	80
	Wall Bullnose Corner	SN-4289M	2-1/8 x 2-1/8	25
	Flat Top Cove Base	A34C1MOD	4-1/4 x 12-7/8	40

## INSTALLATION

Grout Joint Recommendation	Shade Variation
<b>6 x 18 &amp; 8 x 24:</b> 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%.)	 Low (V1)
<b>2 x 8, 4 x 12, &amp; 4 x 16:</b> 1/16" (When rectangular size is installed in a staggered brick joint pattern, overlap should not exceed 33%.)	
<b>4 x 8:</b> 1/16"	

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120-230 lbs
Scratch Hardness	MOHS	4.0-6.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A1371 standards.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).



DESIGNED TO HELP EARN LEED™  
CREDITS. For more detailed information,  
visit [daltilegreenworks.com](http://daltilegreenworks.com).

7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of  
Daltile® products and information,  
visit our website at [daltile.com](http://daltile.com).



IMAGINE WHAT'S POSSIBLE™

©2019 Daltile (1/19)