

STONE LOOK

FLOOR

AMBASSADOR™

COLORBODY™ PORCELAIN PAVERS

XTERIORS™
ALL-WEATHER SOLUTIONS FOR EXTERIOR STYLE



TREAD™
PORCELAIN PAVERS

 dalTile®
IMAGINE WHAT'S POSSIBLE

FLOOR

AMBASSADOR™

COLORBODY™ PORCELAIN PAVERS

Timeless Meets Modern

Inspired by the fine-grained quartzite found in the Swiss Alps, the Ambassador series combines lasting durability with high-end styling. Eons of stratification are reflected in the distinctive mono-directional graining of this ColorBody™ porcelain tile. Large format size in two simplified colors make the series a natural choice for design possibilities in commercial and residential spaces.

- MODERN AND ELEGANT FLAIR
 - Elegant stone look with REVEAL IMAGING® available in two colors featuring a high level of veining and distinctive patterns
 - Modern size 16 x 48, large format size
- HEIGHTENED VERSATILITY
 - Unique pairing available from Verticals™ random linear mosaic adds dimension to this series
 - Pairs with existing Ambassador™ interior floor tile

STONE LOOK

USAGE



SPECIAL FEATURES

SEE CHARTS FOR FULL PRODUCT DETAILS

Cover photo features Ambassador™ Voyager Black pavers.
Above photo features Ambassador™ Jet Setter Dusk pavers.

STONE LOOK

FLOOR
AMBASSADOR™
COLORBODY™ PORCELAIN PAVERS

SIZES:




FINISHES: TEXTURED

COLOR PALETTE




JET SETTER
DUSK



VOYAGER
BLACK



JET SETTER DUSK AM34



VOYAGER BLACK AM33



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT*
*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT*
*Not Applicable to Mesh-Mounted Mosaics



INDOOR/OUTDOOR



SIMPLICLEAN™


VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

AMBASSADOR™






COLORBODY™ PORCELAIN PAVERS

STONE LOOK

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	16 x 48 Paver Tile	(15-9/16" x 47") (39.60 cm x 119.50 cm)	13/16" (2cm)	5.16	1

TRIM†

	Type	Notes
	Rectified Coping	
	Rectified L-Edging	
	Rectified Gutter	† Trim items available in many sizes and colors. Consult with your sales representative and/or design team for specifics.
	Rectified Grid	
	Rectified L-Kerb	

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Dry Laying on Grass:	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
Dry Laying on Gravel:	Gaps of at least 3/16" (4 mm) should be left between slabs, using spacers to set the correct width. Joint may be left empty or filled with fine sand, polymeric sand specifically formulated for porcelain tile or small, clean aggregate, depending on the joint width and desired aesthetic.
Dry Laying on Sand:	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
Laying on Screed with Adhesive:	Slabs must be laid with open joints of variable width of no less than 3/16" (5 mm).
Raised Pavings:	Pedestal contains correct tile spacers for application.

SHADE VARIATION

AM33, AM34



Random (V4) - Considerable Variation from Tile to Tile

PERFORMANCE CHARACTERISTICS

	ASTM#	Paver Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 1000 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: daltille.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.