

WOOD LOOK

FLOOR

COMMISSARY™

COLORBODY™ PORCELAIN PAVERS

**XTERIORS™**  
ALL-WEATHER SOLUTIONS FOR EXTERIOR STYLE

TREAD™  
PORCELAIN PAVERS

 daltile®  
IMAGINE WHAT'S POSSIBLE™

FLOOR

# COMMISSARY™

COLORBODY™ PORCELAIN PAVERS

## Rustic Elegance

With wood-look porcelain pavers from Daltile, you can combine style and performance with unsurpassed durability. Daltile's TREAD™ collection of pavers offers Commissary™ which brings the beauty of the finest natural looking wood to your outdoor living environment. As rich and natural as the inspiration from which it was created, our outdoor pavers offer design solutions with character, strength and a sophisticated contemporary appeal for any project.

- WARM OUTDOOR SOLUTION
  - Multiple wood-look options and patterns
  - Five distinct colors complete any outdoor space
- NATURAL DESIGN POSSIBILITIES
  - Two size offerings, 24 x 24 and 16 x 48, allow various design possibilities to come alive
  - Complement your indoor wood-look tile with the durability of porcelain pavers

WOOD  
LOOK

USAGE



SPECIAL FEATURES

SEE CHARTS FOR FULL  
PRODUCT DETAILS

Cover photo features Commissary™ Regent Honey pavers.  
Above photo features Commissary™ Proxy Grey pavers.

SIZES:



FINISHES: TEXTURED


COLOR PALETTE




REGENT HONEY



COMMANDER BEIGE



DEPUTY GREY



PROXY GREY



BUREAU BROWN



DEPUTY GREY CS30



REGENT HONEY CS34



PROXY GREY CS31



COMMANDER BEIGE CS32



BUREAU BROWN CS33



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT\*  
\*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT\*  
\*Not Applicable to Mesh-Mounted Mosaics





INDOOR/OUTDOOR








SIMPLICLEAN™

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 24* Paver Tile	(23-7/16" x 23-7/16") (59.50 cm x 59.50 cm)	13/16" (2cm)	7.76	2
	16 x 48 Paver Tile	(15-9/16" x 47") (39.60 cm x 119.50 cm)	13/16" (2cm)	5.16	1

\* Available in colors CS30 and CS34 only

## TRIM†

Type	Notes
	Rectified Coping
	Rectified L-Edging
	Rectified Gutter
	Rectified Grid
	Rectified L-Kerb

† Trim items available in many sizes and colors. Consult with your sales representative and/or design team for specifics.

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).




### APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

## INSTALLATION

<b>Dry Laying on Grass:</b>	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
<b>Dry Laying on Gravel:</b>	Gaps of at least 3/16" (4 mm) should be left between slabs, using spacers to set the correct width. Joint may be left empty or filled with fine sand, polymeric sand specifically formulated for porcelain tile or small, clean aggregate, depending on the joint width and desired aesthetic.
<b>Dry Laying on Sand:</b>	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
<b>Laying on Screed with Adhesive:</b>	Slabs must be laid with open joints of variable width of no less than 3/16" (5 mm).
<b>Raised Pavings:</b>	Pedestal contains correct tile spacers for application.

## SHADE VARIATION

CS30, CS34		Medium (V2) - Color Variation within each Tile
CS32		High (V3) - Some Variation from Tile to Tile, and within each Tile
CS31, CS33		Random (V4) - Considerable Variation from Tile to Tile

## PERFORMANCE CHARACTERISTICS

	ASTM#	Paver Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 1000 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

### PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit [daltile.com](http://daltile.com).