



STONE LOOK

FLOOR

**ASTRONOMY™**

COLORBODY™ PORCELAIN with STEPWISE™



 **daltile®**  
IMAGINE WHAT'S POSSIBLE™

FLOOR

# ASTRONOMY™

COLORBODY™ PORCELAIN with STEPWISE™

## Cosmic Design

Inspired by a view into deep space, this porcelain tile represents the crossroads of practicality and dreams. Sprinkled with stardust, Astronomy features ColorBody™ Porcelain and StepWise™ technologies in a matte limestone look. Available in four mystical tones in your favorite sizes.

- **STELLAR DESIGN**
  - Inspired by limestone
  - Starring in four neutral colors
  - Offered in two floor tile sizes with coordinating trim option
- **TAKE IT OUTSIDE**
  - StepWise™ technology for increased slip-resistance
  - Floor tile with StepWise™ technology is suitable for most exterior applications
  - Suitable for both Residential and Commercial spaces

STONE  
LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER  
FLOOR



EXTERIOR  
FLOOR



STEPWISE™



TRU-EDGE™



MADE IN  
THE U.S.A.



LARGE  
FORMAT



MOSAIC/  
DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



PC  
COLORBODY  
PORCELAIN

LOW

HIGH

SEE CHARTS FOR FULL  
PRODUCT DETAILS

Cover and above photos feature Astronomy™ Orion 12 x 24 on the floor with Panoramic Gypsum Calacatta and Chromium matte on the countertops and Gypsum Calacatta glossy on the wall.

STONE LOOK

FLOOR  
**ASTRONOMY™**  
COLORBODY™ PORCELAIN with STEPWISE™

SIZES:



FINISHES: MATTE

COLORBODY™ PORCELAIN FLOOR TILE with STEPWISE™



ECLIPSE AT70



ORION AT71



SOLSTICE AT72



NEBULA AT73

**50% MORE**  
SLIP RESISTANT  
THAN ORDINARY TILE\*

\*When compared to tile meeting ANSI standards.



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT<sup>†</sup>  
<sup>†</sup>Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT<sup>†</sup>  
<sup>†</sup>Not Applicable to Mesh-Mounted Mosaics



INDOOR/OUTDOOR



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT [WWW.DAL TILE.COM](http://WWW.DAL TILE.COM) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.



## ALL STYLE. NO SLIPS.

Don't tip-toe through life. Step stylishly on non-slip tile that's 50% more slip resistant than ordinary tile. And because it's Daltile, you'll find beautiful natural looks that are waterproof, scratchproof, stainproof and dentproof.

### SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	12 x 24 Floor Tile	(11-13/16" x 23-13/16") (30.00 cm x 60.48 cm)	5/16"	15.60	8
	18 x 18 Floor Tile	(17-3/4" x 17-3/4") (45.20 cm x 45.20 cm)	5/16"	17.60	8

### APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

#### APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

### TRIM

Type	Number	Size	Pieces/ Carton
Bullnose	P-43F9	3 x 24	10
Cove Base	P-36C9TB	6 x 12	22
Cove Base Outcorner	PC-36C9TB	6 x 1	15

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

Cove base and cove corner trim are suitable for non-freezing climates only.

### INSTALLATION

Grout Joint Recommendation	Shade Variation
<b>Floor:</b> 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	Medium (V2)

### PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

### DURABILITY

#### Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	④ All Residential / Commercial

### NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [daltile.com/LargeTiles](http://daltile.com/LargeTiles) for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

**PRE-CONSUMER RECYCLED MATERIALS**

**MADE IN THE U.S.A.**

**REVEAL IMAGING®**

All or select items within this series meet the requirements for these qualifications. For more information, visit [daltile.com](http://daltile.com).