

WALL



AESTHETIC™
GLAZED CERAMIC



AESTHETIC™

GLAZED CERAMIC

Design in Motion

Create striking dimension in your space with Aesthetic™. With patterns ranging from organic, natural visuals to structured, geometric textures, this large format 12x36 wall tile is designed to flow seamlessly from tile to tile. Available in a simple yet rich and elegant white, the structure is sure to be the focal point of your space.

- SEAMLESS DESIGN
 - Captivating structures create contemporary and stunning feature walls
 - Seven distinct patterns designed for continuous flow from tile to tile
- EXCLUSIVE FORMATS
 - Available in a large format 12x36 wall tile
 - A stand-alone, simple yet rich and elegant, white color offering



Cover photo features Aesthetic™ Arrow 12 x 36 on the wall and Revotile™ Graphite 12 x 24 on the floor. Above photo features Aesthetic™ Geometric 12 x 36 on the wall and Famed™ Luxe 12 x 24 on the floor.

WALL

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



GLAZED CERAMIC



LOW HIGH

SPECIAL FEATURES

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES:



FINISHES: SATIN | GLOSSY



TRIBAL AS24 – SATIN



ARROW AS25 – SATIN



FREQUENCY AS22 – SATIN




GEOMETRIC AS23 – SATIN



HONEYCOMB AS27 – SATIN



RETROCUBE AS26 – SATIN



FLAT AS20 – SATIN
FLAT AS21 – GLOSSY



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



SIMPLICLEAN™

AESTHETIC™

GLAZED CERAMIC

WALL

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
	12 x 36 Wall Tile (11-13/16" x 35-1/2") (30.00 cm x 90.20 cm)	AS23, AS24, AS25, & AS27: 7/16"	17.44	6
		AS22 & AS26: 1/2"		
		AS20 & AS21: 3/8"		

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%.)	 Low (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	> 120 lbs
Scratch Hardness	MOHS	4.0 - 6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

ZEROTOX

Healthy Homes | Healthy Planet

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltile.com.

daltile®

IMAGINE WHAT'S POSSIBLE™

©2021 Daltile (6/21)