



WOOD LOOK

TRANSIO™
GLAZED PORCELAIN



 daltile®
IMAGINE WHAT'S POSSIBLE™

TRANSIO™

GLAZED PORCELAIN

Historic Transcendence

Transio™ celebrates tradition by honoring the classic look of wood in a modern color palette. Four colors give you the choice of time-honored browns and a contemporary light beige and grey. The large 8x47 tile plank along with rich graphics allow for natural-looking variation in your space. Leave a legacy of cultured elegance when you design with Transio™.

- CELEBRATE TRADITION
 - Genuine look of wood
 - Color palette includes classic browns and modern beige and grey
- PLANK VARIATION
 - Available in a large, rectified 8x47 tile plank
 - Each color offers 27 graphic faces for natural-looking variation

WOOD
LOOK

USAGE



SPECIAL FEATURES

SEE CHARTS FOR FULL
PRODUCT DETAILS

Cover photo features Perpetuo™ Timeless White hexagon mosaic on the backsplash and Transio™ Prevail 8 x 47 on the floor.
Above photo features Memoir™ Crystal Grey 12 x 12 on the wall and Transio™ Conquest 8 x 47 on the floor.

WOOD LOOK

TRANSIO™
GLAZED PORCELAIN

SIZES:

8 x 47
Floor Tile

FINISHES: MATTE



PREVAIL TN12



CONQUEST TN10



TRIUMPH TN11



THRIVE TN13



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT




CLIMATEPRO™



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
 8 x 47 Floor Tile	(7-5/8" x 46-1/2") (19.40 cm x 118.20 cm)	7/16"	14.75	6

APPLICATIONS


	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	 High (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltille.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance		
1 Residential Bathrooms (3)	All Residential / Light Commercial	
2 All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltille.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit daltille.com.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.