4.5 mm | 12 Mil
ADVENTURO™
RIGID CLICK

PROSERIES LUXURY VINYL FLOORING Natible







4.5 mm | 12 Mil ADVENTURO™ RIGID CLICK

ADVENTURE AWAITS

Experience a premier luxury vinyl floor with the captivating wood tones available in Adventuro™. Unmatched in design and technology, this ultra durable, rigid core plank leads to a superior floor that clicks together with ease and speed.

Cascading in design, these wood looks provide high-graphic variation and texture alongside enhanced performance and quick Uniclic® locking installation. Excellent thermal insulation and superior sound attenuation are just a few of the perks of this high-performing product.

BRILLIANT DESIGN

- 6" x 48" wood look planks
- 12 adventurous colors
- Textured surface for realistic look and fee
- HD design with medium and high-variation
- Multi-layer SPC rigid core with Uniclic® Locking System
- Built-in solid IXPE underlayment pad that resists mold and mildew
- 4.5 mm Thickness

TOP-RANK DURABILITY

- SuperGuard™ Technology 12 Mil wear layer for heavy foot traffic
- 100% Waterproof
- 100% Virgin Vi<mark>nyl</mark>
- 7 Year light commercial warranty 30 Year residential warranty

| SIZES:

6 x 48 Plank

6 x 48 WOOD LOOK PLANKS



INTREPID AD39



TREKKER AD38



ARC AD35



MARINER AD41



WANDER AD37



EXPLORER AD36



FOREST AD34



TRAVELER AD30



COMPASS AD33



VOYAGE AD31



WILDE AD40



JOURNEY AD32

4.5 mm | 12 Mil ADVENTURO™ RIGID CLICK

SPECIFICATIONS

Product Type: SPC Rigid Core LVF

Installation: Click
Thickness: 4.5 mm

Wear Layer: 12 Mil (0.3048 mm)

Finish: SuperGuard™ Technology

Size: 6" W x 48" L Plank

Underlayment: Pad Attached; 1.0 mm IXPE Closed Cell

Bevel: Micro-Bevel
Plank Variation: 6 Unique Planks

Sq. Ft./Carton: 32.15 Pieces/Carton: 16

Weight 2.80 lbs per pc / 45.74 lbs per carton
Installation Adventuro™ click LVF uses Uniclic®
Advisory: Locking System; no adhesive required.

Locking System; no adhesive required. See daltile.com/LVF for more recommended

installation information.

Transitions: Click LVF transitions are offered in a

Vinyl 4-in-1, Flush Mount Vinyl Stair Cap and Overlap Vinyl Stair Nose. Can be installed with or without underlayment, when total installation is 8.0 mm or less. See daltile.com/LVF for more information.

Warranty: Limited 7 Year Light Commercial Warranty

Limited 30 Year Residential Warranty

PERFORMANCE & CHARACTERISTICS

Construction: Commercial Grade Luxury Vinyl Flooring;

100% Virgin Vinyl

Classification: ASTM F1700 - Class III, Type A - Smooth,

Type B - Embossed

Squareness: ASTM F2421 - Passes - ±0.010" max

Size and Tolerance: ASTM F2421 - Passes - ±0.016 in. / linear foot

Thickness: ASTM F386 - Passes - ±0.13 mm

Flexibility: ASTM F137 - Passes - 1" mandrel

Dimensional Stability: ASTM F2199 - Passes - < 0.25% / linear foot

Static Load Limit: ASTM F970 - Passes, Test to Limit (+0.005")

Residual Indentation: ASTM F1914 - Passes - Average < 8.0%

Resistance To Chemicals: ASTM F925 - Passes - ≤1 Slight Change

Resistance To Light: ASTM F1515 - Passes - $\Delta E \le 8$

NOTES

Resistance To Heat:

See daltile.com/LVF for recommended installation and care guidelines

ASTM F1514 - Passes - ∆E ≤ 8







daltile






Three trims and moldings that are designed to coordinate wiyth each of our existing colors within the collection.

- **VSNP** Overlap Stair Nose (2" x 79")


- **VSCAP** Flush-Mount Vinyl Stair Cap (2-3/4" x 44")

- **V4IN1** Four Unique Trims and mouldings in one single SKU (2" x 79") (T-Molding, Hard Surface Reducer, Carpet Transition, End Molding)




Overlap Stair Nose

Creates a transition to the edge of the step by overlapping the flooring on the back end instead of being flush.



Vinyl Stair Cap

Creates a smooth and flush finish on the edges of steps by using the same vinyl flooring plank to ensure a corresponding color and texture.



4-in-1 Transition

Performance Accessories' exclusive 4-in-1 transition allows you to utilize a single transition for four different applications.

EACH OF THE BELOW ARE ACHIEVED VIA THE V4IN1 TRANSITION (SHOWN ABOVE)



T-Molding

Used to transition between flooring of equal heights and in doorways.



Hard Surface Reducer

Connects two floors of different heights.



End Molding

Created a smooth and flush finish on the edges of steps where the flooring meets the transition.



Carpet Transition

Provides a smooth transition between your hard surface floor and carpet.



