3.0mm | 8 mil HARPER'S PLACE™ FLEXIBLE GLUE DOWN WITH ACOUSTICAL PAD ATTACHED

LUXURY VINYL FLOORING

8 daltile





3.0mm | 8 mil HARPER'S PLACE™ FLEXIBLE GLUE DOWN WITH ACOUSTICAL PAD ATTACHED HARPER'S PLACE™ Designed with the modern metropolitan in mind, Harper's Place™ is fabricated with noise-reducing technology to preserve an atmosphere of tranquility amidst the bustle of city life. This luxury vinyl flooring is available in a wide variety of shades, spanning from cool to warm tones

and all offered in a lengthy 7.5" x 48.5" plank. Built with SuperGuard™ to withstand everyday foot traffic, Harper's Place maintains its elegance long-term.

LUXURIOUS DESIGN

- 7.5" x 48.5" wood look planks
- Cool to warm tone color palette
- Flexible Glue Down with acoustical pad attached
- Embossed for realistic look and feel
- Built-in solid IXPE underlayment pad that resists mold and mildew
- 3.0 mm Thickness

PROVEN DURABILITY

- SuperGuard™ Technology
- 8 mil wear layer for heavy foot traffic
- 100% Waterproof
- 100% Virgin Vinyl
- Limited 20 Year Residential Warranty
- Limited 3 Year Multifamily Warranty

HARPER'S PLACE™

FLEXIBLE GLUE DOWN WITH ACOUSTICAL PAD ATTACHED

| SIZES: | |
|--------|----------------|
| | 7-1/2 x 48-1/2 |

7.5 x 48.5 WOOD LOOK PLANKS





3.0mm | 8 mil HARPER'S PLACE™









FLEXIBLE GLUE DOWN WITH ACOUSTICAL PAD ATTACHED

SPECIFICATIONS

Product Type: Flexible Glue Down with acoustical pad attached

Installation: Flexible Glue Down

Thickness: 3.0 mm

Wear Layer: 8 mil (0.2032 mm)

Finish: SuperGuard™ Technology
Size: 7-1/2" W x 48-1/2" L Plank
Underlayment: Pad Attached; 1.0 mm IXPE

Bevel: No Bevel

Embossing: Embossed

Plank Variation: 5 Unique Planks

Sq. Ft./Carton: 40.64

Pieces/Carton: 16 pcs/carton

Weight

1.89 lbs per pc / 30.24 lbs per carton

Warranty:

Limited 20 Year Residential Warranty

Limited 3 Year Multifamily Unit Warranty

Installation Glue Down LVF must be installed using ProSeries by Daltile Adhesive. See daltile.com/LVF for more recommended

Advisory: installation and adhesive information.

Stocking Platform: 3 mm, 8 mil

Special order Platform: Additional Platforms available on special order. Minimum quantities apply. Contact your Daltile representative for

additional information.

PERFORMANCE & CHARACTERISTICS

Construction: Commercial Grade Luxury Vinyl Flooring; 100% Virgin Vinyl

Classification: ASTM F1700-Class III, Type A-Smooth, Type B-Embossed

Squareness: ASTM F2421 - Passes - \pm 0.010" max

Size and Tolerance: ASTM F2421 - Passes - Plank Length \geq 48 in. \pm 0.080 in. (2 mm)

Thickness: ASTM F386 - Passes - ± 0.118 inches

Flexibility: ASTM F137 - Passe - 1 in. (25.4-mm) mandrel, no crack or break

Dimensional Stability: ASTM F2199 - Passes - 0.020 in./lin. Ft (0.51mm/ 305 mm) maximum

Residual Indentation: ASTM 1914 - Passes - Average < 8.0 %

Resistance To Chemicals: ASTM F925 - Passes - ≤ 1 Slight Change

Resistance To Light: ASTM F1515 - Passes - $\Delta E \le 8$ Resistance To Heat: ASTM F1514 - Passes - $\Delta E \le 8$

NOTES

See daltile.com/LVF for recommended installation and care guidelines.





