STONE LOOK

DIPLOMACY™

STONE ATTACHE" COLLECTION - COLORBODY" PORCELAIN



DIPLOMACY[™]

STONE ATTACHE[™] COLLECTION - COLORBODY[™] PORCELAIN

Bluestone Allure

Diplomacy deftly delivers the quiet strength and visual beauty of quarried Belgian bluestone. Diplomacy is available in three smoky hues that come alive with movement created by delicate highlights of light greys and whites. Large format floor tiles paired with a coordinating brick-joint mosaic create a magnificent space crowned by an authentic stone look.

- BLUESTONE BRILLIANCE
 - Natural look of quarried Belgian bluestone in durable ColorBody[™] porcelain tile
 - Three smoky, grey tonalities in a brushed stone surface
- DESIGN SELECTION
 - Three floor tile sizes including a 24 x 48 brick-joint mosaic and trim package also available
 - Rectified edges for smaller grout joint installation



Cover photo features Diplomacy[™] Dark Grey 24 x 24 on the floor. Above photo features Diplomacy[™] Dark Grey brick-joint mosaic on the wall.



STONE LOOK

DIPLOMACY[™]

FINISHES: MATTE | TEXTURED

STONE ATTACHE[™] COLLECTION - COLORBODY[™] PORCELAIN



FLOOR TILE






LIGHT GREY DP01



DARK GREY DP03

BRICK-JOINT MOSAIC



LIGHT GREY DP01









MEDIUM GREY DP02









STAINPROOF

DENTPROOF

SCRATCH-RESISTANT

DARK GREY DP03

VISIT THE WHY TILE PAGE AT WWW.DALTILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

INDOOR/OUTDOOR

51215					
			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 48 Floor Tile	(23-7/16" x 47") (59.50 cm x 119.30 cm)	3/8"	15.50	2
	20 x 40 Paver Tile	(19-1/2" x 39-3/16") (49.50 cm x 99.50 cm)	13/16"	5.38	1
	24 x 24 Floor Tile	(23-7/16" x 23-7/16") (59.50 cm x 59.50 cm)	3/8"	11.64	3
	24 x 24 Paver Tile*	(23-7/16" x 23-7/16") (59.50 cm x 59.50 cm)	13/16"	7.76	2
	12 x 24 Floor Tile	(11-11/16" x 23-7/16") (29.65 cm x 59.50 cm)	3/8"	9.70	5
		(11-11/16" x 11-11/16" Sheet) : (29.65 cm x 29.65 cm Sheet)	3/8"	3.88	4

* 24 x 24 Paver is available by special order with standard leadtime of 60-90 days.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	~
Wet & Level – Interior Floor	≥ 0.42	~
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	v **
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	~
Countertops	N/A	~
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest[™], visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

* Mosaic tile only.

** Paver tile only.





All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

TRIM

Туре	Number	Size	Pieces/ Carton
Bullnose	S43F9	3 x 24	15

Floor bullnose trim is intended to coordinate with floor tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	Medium (V2)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 300 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance				
1	Residential Bathrooms	3	All Residential / Light Commercial	
2	All Residential Areas	4	All Residential / Commercial	

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.







7834 C.F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.





ву 💦 daltile





DIPLOMACY[™] COLORBODY[™] PORCELAIN PAVERS

Bluestone Allure

Diplomacy deftly delivers the quiet strength and visual beauty of quarried Belgian bluestone. Diplomacy is available in two complementary hues that come alive with movement created by delicate highlights of light greys and whites. Large format 2CM porcelain paver tiles pair with existing 3/8" interior tile for a seamless transition from interior to exterior. For the crowning touch a coordinating brick-joint mosaic creates a magnificent space completing the authentic stone look.

- BLUESTONE BRILLIANCE
 - Natural look of quarried Belgian bluestone in durable 2CM ColorBody[™] porcelain paver tile
 - Two smoky grey tonalities in a brushed stone surface
- DESIGN SELECTION
 - Unique pairing available from Verticals random linear mosaic adds dimension to this series
 - Two paver sizes available 20 x 40 and 20 x 20* in 2cm thickness for exterior applications
 - Brick-joint mosaic and trim package to complete the look
 - Rectified edges for smaller joints

STONE

LOOK

£)

ARGE

PAVER

* Special Order available

Cover photo features Diplomacy Light Grey pavers-Above photo features Diplomacy Light Grey & Dark Grey pa

DIPLOMACY[™]

COLORBODY[™] PORCELAIN PAVERS






COLOR PALETTE







LIGHT GREY DP01



DARK GREY DP03















VISIT THE WHY TILE PAGE AT WWW.DALTILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
24 x 24 Paver Tile⁺	(23-7/16" x 23-7/16") (59.50 cm x 59.50 cm)	13/16" (2cm)	7.76	2
20 x 40 Paver Tile	(19-1/2" x 39-3/16") (49.50 cm x 99.50 cm)	13/16" (2cm)	5.38	1

*Special Order with a Standard Lead Time: 60 - 90 Days

TRIM[†]

	Туре	Notes
\bigcirc	Rectified Step Nose	
	Coping	 [†] Trim items available in many
	Rectified Gutter	sizes and colors. Consult with your sales representative and/
	Rectified Grid	 or design team for specifics.
	Rectified L-Kerb	_

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	~
Wet & Level – Interior Floor	≥ 0.42	~
Shower Floors (Residential or Light Commercial)	≥ 0.42	~
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	\checkmark
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	\checkmark
Countertops	N/A	\checkmark
Pool Linings	N/A	

A DCOF value of \geq 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest[®], visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Dry Laying on Grass:	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
Dry Laying on Gravel:	Gaps of at least 3/16" (4 mm) should be left between slabs, using spacers to set the correct width. Joint may be left empty or filled with fine sand, polymeric sand specifically formulated for porcelain tile or small, clean aggregate, depending on the joint width and desired aesthetic.
Dry Laying on Sand:	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
Laying on Screed with Adhesive:	Slabs must be laid with open joints of variable width of no less than 3/16" (5 mm).
Raised Pavings:	Pedestal contains correct tile spacers for application.

SHADE VARIATION

DP01, DP03

Medium (V2) - Color Variation within each Tile

PERFORMANCE CHARACTERISTICS

	ASTM#	Paver Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 1000 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.







LEARN MORE

7834 C.F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.

