

MOSAIC

2

2-12

## PERFIT MOSAIX<sup>TM</sup> NATURAL STONE

2 2

2



## **PERFIT MOSAIX<sup>™</sup>**

NATURAL STONE

Cut your installation time in half with Perfit Mosaix<sup>™</sup> - our striking 18″ mosaic collection created to perfectly fit most kitchen backsplashes. Ranging from MOSAIC genuine marble to quality glass, each in a thoughtfully unique shape, Perfit Mosaix offers custom elegance with minimal labor. 10SAIC/ DECO Cover photo features Perfit Mosaix" Dash Mosaic on the backsplash, Adventuro" Mariner 6 x 48 matte on the floor and Natural Stone Granite Summit White Polished on the countertop. ALLE Above photo features Perfit Mosaix<sup>®</sup> Capsule Mosaic polished on the backsplash, ONE Quartz Surfaces® Statuary Glory polished on the countertop, and Rhetoric<sup>®</sup> Aristotle White 12 x 24 matte tile on the floor.

# PERFIT MOSAIX<sup>™</sup>

NATURAL STONE



#### NATURAL STONE & GLASS MOSAICS



1 X 1 BRICK JOINT MOSAIC PT48 White Carrara & Glass Polished



1x4 STRAIGHT STACK MOSAIC PT52 White Carrara & Glass Polished



1 X 2 BRICK JOINT MOSAIC PT49 White Carrara & Glass Polished



SPLIT FACE RANDOM LINEAR MOSAIC PT53 White Carrara & Glass



2x2 STRAIGHT STACK MOSAIC PT50 Marmara & Glass Polished



RANDOM LINEAR MOSAIC PT51 Marmara & Glass Polished

### NOTES

Natural stone products inherently lack uniformity and are subject to variation in aesthetics (color, shade, finish, etc.) and performance (hardness, strength, slip resistance, etc.). Natural stone products do not meet minimum coefficient of friction thresholds recommended by safety standard setting organizations. No warranties, expressed or implied, relative to merchantability or fitness for a particular purpose are made regarding the natural stone products distributed by Dal-Tile. Check local building codes prior to specification or installation to verify that product technical characteristics comply with required parameters.

Polished surfaces are not recommended for floor areas where slip resistance is a concern. Our durability recommendations are only based on the technical characteristics of the stones, however, slip resistance shall still be taken into cons ideration when selecting the product for a specific application. Natural stone products do not meet minimum coefficient of friction thresholds recommended by safety standard setting organizations.

The existence and dimensions of a bevel may vary from lot to lot. Be sure to request a sample of the

specific lot you are planning to order if the bevel is an important feature of your job.

For additional application and technical information, refer to the "Stone Usage Guide" at daltile.com/sug.



7834 C.F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile<sup>®</sup> products and information, visit our website at **daltile.com**.



LEARN MORE