D520010T

Job Name: _

Contractor: __



D520010T

SPECIFICATIONS

PRINCE[™] TRIM ONLY SINGLE HANDLE PRESSURE BALANCE TUB & SHOWER FAUCET

Flow Rate Model D520010T 9 Description 7 GPM • 4" bell style showerhead 5 • All brass 6" shower arm 3 · Diverter on spout 1 Use with valve: D112000BT (w/stops) or D115000BT 20 40 60 80 (w/o stops) PSI **Standards** • UPC/cUPC • Energy Policy Act of 1992 • ASME A112.18.1 MEETS ASME A112.18.1 ADA Accessibility Guidelines for Buildings and Facilities -**Finishes Available** 4.27.4 Controls and Mechanisms Chrome • Other: Refer to Price List for additional finish Warranty Danze products are covered by a manufacturer's limited "lifetime" warranty for manufacturing defects. 7 3/16" 1/2"-14NPT (182mm) Ŵ (111mm) 4 3/8" Ø60mm) Ø2 3/8" Ø7 3/16" (Ø16mm) (Ø182mm) Ø5/8" Ø3 1/16" (Ø77mm) 1 1/2"~2" (1651-1981mm) (38mm~51mm) (111mm) 4 3/8" 65"-78" 1/2"-14NPT Ø80mm) Ø3 1/8" 11111111111 (838mm) 33" 1 7/8 (48mm) (508mm) 4 13/16' 20" (123mm) Submittal Information:

Location: _

Contact #:_

