
6000 / 6000-DA SERIES MEDIUM-HEAVY DOOR CLOSER



DIMENSIONS



PRODUCT SPECIFICATIONS

- Meets ANSI 156.4 Grade 1
- UL / UL10C Listed
- · Compliant with ADA reduced opening force requirements
- Universal 12" Horizontal Mounting Hole Pattern
- Fully adjustable power size 1~6. Factory preset Size 3
- Independent Latch, Sweep, & Backcheck Intensity Valve
- Heavy Duty Rack & Pinion
- Heat treated High Tension Piston
- High lubricity hydraulic fluid to ensure smooth operation
- 6000-DA equipped w/ Delay Action feature
- Standard arm and parallel bracket included for regular arm, top jamb, and parallel arm applications
- · Standard full cover
- Non-Handed



RECOMMENDATIONS												
DOOR CLOSER WEIGHT			MAXIMUM SIZE OF DOOR									
	Door Weight	Duty	Power Size	Regular Arm			Parallel Arm					
Series				Interior	Exterior Swing-In	Exterior Swing-Out	Interior	Exterior Swing-Out				
6000	55-330 Lbs	Medium-Heavy	1	28"	N/A	N/A	N/A	N/A				
			2	36"	N/A	N/A	30"	N/A				
			3	42"	30"	36"	36"	30"				
			4	48"	36"	42"	42"	36"				
			5	54"	42"	48"	48"	42"				
			6	60"	48"	54"	54"	48"				

PRICING

Model	WT/ CTN	WT/ CTN		Aluminum	Duro	Gold	
6000 Series Door Closer	44 Lbs.	4 Pcs	Item No.	606710	606711	-	
with Standard Full Cover			List Price				
6000 Series Door Closer with Delay Action	44 Lbs.	4 Pcs	Item No.	606740	606741	606742	
(DA) & Standard Full Cover			List Price				

OPTIONAL FEATURES

- Hold open arm with parallel bracket
- Parallel rigid arm
- Hold Open CUSH arm
- Thru bolts for metal door mounting
 - Drop plates

