

Electronic Faucets

4" Cast Deck mount electronic Proximity® Sensing Technology lavatory faucet - hi-rise spout

Model No: 591TP0228TR

COMPLIES WITH:

- CSA certified
- Complies to ASME A112.18.1/ CSA B125.1
- Lindicates compliance to ICC/ANSI A117.1
- Verified compliant with 0.25% weighted average Pb content regulations
- Patented
- NOTE 1: For optimum performance of this product, we recommend a system pressure between 20 and 80 PSI static. This product will operate up to a maximum of 125 PSI static per ANSI and CSA requirements. However, we do not recommend pressures above 80 PSI. Thermal expansion or leaking pressure reducing valves may require use of expansion tanks or relief valves to ensure your system never exceeds its maximum intended pressure setting.
- NOTE 2: Use 3-conductor 18AWG wire between transformer and hardwire converter/driver board earth ground.
- NOTE 3: Use Delta Commercial approved transformers and mount the transformer a minimum of 6 inches away from the Delta driver board enclosure.
- NOTE 4: Refer to Proximity Application Notes for installation best practices, proper grounding and wiring diagrams on www.specselect.com.
- NOTE 5: High temperature disinfection cycles not recommended for #8
 Control Box as the thermostatic mixing valve limits the higher temperature water flow output.
- NOTE 3: Hardwire Proximity models not for use on enamel covered metal sinks
- Outlet options 2, 3 and 6 are EPA WaterSense listed
- (Contact Delta Representative for State and/or Local Approvals)







NOTES:

Control Box(590Txxx8TR) - NOTES: Requires Rough-in Product Number ELAVT0008ARI to be ordered separately seeELAVT0008ARI

SPECIFICATION:

- Proximity® Sensing Technology
- Chrome plated CAST 102 mm (4") spout body
- Adjustable sensing range and timeout
- Mixing valve required (order separately)
- Serviceable filter screen upstream of the solenoid valve
- Metal hold-down package
- Supplied as complete product
- Outlet#: 2 Vandal Res.1.5 GPM (5.7 L/Min) Laminar w/Agion® Antimicrobial
- Supplied as trim parts only requires separate order of ELAVT0008ARI rough-in to have complete product
- (24 VAC) Hardwire powered by Class II transformer (purchased separately)
- Hardwire Version comes complete with watertight connector and Hardwire Converter 24VAC to 6VDC
- 4" (102mm) Cast Electronic Faucet


OPERATION:

- Hands free (touchless) operation.
- No visible sensor, the spout is the sensor.
- Water flows when sensing is activated.
- Water flow stops upon de-activiation of sensing.
- Adjustable sensing distance factory set to 76 mm (3").
- Low battery audible beep (for battery models only) will activate after faucet shuts off when approximately 1500 cycles remain.
- Adjustable auto shut off feature. Factory set to 45 seconds.
- Metering mode with selectable flow times of 7 seconds to 4 minutes, factory set off.
- Periodic Rinse feature, time adjustable in 6 hour increments up to 2 days.
 Selectable rinsing lengths from 10 to 180 seconds. Factory set off.

(Dimensional drawing on following page)

Delta reserves the right (1) to make changes to specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference. Measurement may vary plus or minus 6mm(0.25"). Mounting locations are suggested only. Check with local codes for requirements in your area. This spec was produced January 20, 2017.





Delta reserves the right (1) to make changes to specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference. Measurement may vary plus or minus 6mm(0.25"). Mounting locations are suggested only. Check with local codes for requirements in your area. This spec was produced January 20, 2017.