

### ▲ Designate proper finish suffix

Your Delta Faucet handshower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.



see what Delta can do

# PERSONAL HAND HELD SHOWERS

- Certified Dual Check Valves
- Shower Arm or Wall Mount

### STANDARD SPECIFICATIONS:

- Handheld shower with one to four settings pause is a non-positive shut-off
- 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- 60" (1524 mm) stainless steel hose (54471-18-BG)
- 60"-82" (1524 mm 2083 mm) stretchable metal hose: 59310-18-PK, 59344-B18-PK, 59348-18-PK
- Includes double check valves for backflow prevention
- Shower arm mount: 54471, 59344
- Wall mount: 59310, 59348
- Handhower only: 59465-18-PK
- ADA compliant handshower when installed per accessibility guidelines of the act (59344-18-PK only)

# **WARRANTY**

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or for commercial users, for 5 years from the date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



## **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1 ◆ Indicates compliance to ICC/ANSI A117.1
- EPA WaterSense®