

# 620TPA3328TR

## Description

Introducing our premium model boasting a flow rate of 1.5 gpm (5.7 L/min) and a sleek chrome finish. Equipped with Proximity® Sensing Technology, it operates seamlessly with hardwire power supply (24 VAC). Designed for deck mounting, its gooseneck spout offers both style and functionality, providing precise water flow. The fixture includes trim parts only, featuring a stainless steel cover, solenoid, hardwire converter, and driver board, with the option for an 8 = Trim ONLY configuration for a recessed box setup (rough-in, AC filter, and transformer sold separately).

## Specifications

- Flow Rate: 1.5 gpm (5.7 L/min)
- Spray Type: Laminar
- Sensor Type: Proximity® Sensing Technology
- Power Supply: Hardwire Operated (24 VAC)
- Finish: Chrome
- Mounting Type: Deck Mount
- Spout Type: Gooseneck Spout
- Control Box: 8 = Trim ONLY for Recessed Box (rough-in, AC filter and transformer sold separately)
- Solenoid and Controller in Surface Mount Housing
- Supplied as Trim Parts ONLY (includes Stainless Steel Cover, Solenoid, Hardwire Converter and Driver Board)

## Features

- Hands-free Operation - Allows for touchless operation, promoting hygiene and convenience
- Proximity® Sensing Technology - No visible sensor, the spout is the sensor
- Adjustable Sensing Range and Timeout - Customize sensing range and timeout settings based on specific preferences and needs
- Serviceable Filter Screen - Equipped with a conveniently serviceable filter screen located upstream of the solenoid valve
- Single Hole Installation

## Required Accessories

- 063271A - AC Filter for up to 5 Proximity® Faucets
- 063267A - AC Filter & Transformer 20VA, 120/24Vac for up to 5 Proximity® Faucets
- 060704A - Transformer 20VA, 120/24Vac for up to 5 Units
- 060771A - Transformer 40VA, 120/24Vac for up to 10 Units
- ELAVT0008ARI - Rough-in with R2570-MIXLF Thermostatic Mixing Valve
- ELAVT0001ARI - Rough-in Requires R2570-MIXLF or R3270-MIXLF

## Optional Accessories

- 061269A - 4" (102 mm) Cover Plate (Chrome)
- 061256A - 36" (91 cm) Sensor Extension Cable
- 063269A - Battery Backup Assembly for Recessed Boxes
- 060651A - 3 Position Switch

## Notes

- Designed to accommodate routine 180°F (82°C) disinfection cycles lasting up to 10 minutes
- Use only Delta® supplied cable sets. Using non-Delta® cables, cutting or splitting any components will void the warranty
- Compatibility: Proximity® models are not suitable for use on enamel-covered metal sinks
- Use 2-conductor 18 AWG wire for all electrical connections
- Use Delta® Commercial approved AC filters and transformers



## Complies With

- ASME A112.18.1/CSA B125.1
- ICC / ANSI A117.1
- EPA WaterSense listed
- Verified compliant with 0.25% weighted average Pb content regulations



(Contact Delta Representative for State and/or Local Approvals)

## Operation

- Hands-Free Operation - No visible sensor, the spout is the sensor - Water flows when sensing is activated - Water flow stops promptly upon deactivation of sensing
- Adjustable Auto Shut-off - The auto shut-off feature is adjustable, with a factory setting of 45 seconds
- Adjustable Sensing Distance - Sensing distance can be customized from 3" to 15" (76 to 381 mm) - The factory setting is 3" (76 mm)
- Metering Mode - Offers selectable flow times ranging from 7 seconds to 4 minutes - Factory setting is off
- Periodic Rinse Feature - Time for periodic rinse is adjustable in 6-hour increments, up to 2 days - Selectable rinsing lengths range from 10 to 180 seconds - Factory setting is off
- Single Tempered Water Supply Requirement - Ensures optimal operation by necessitating a single tempered water supply
- Maximum combination of 5 faucets can be connected to 1 AC Filter

**NOTICE** Dimensions are for reference only. Measurements may vary  $\pm 0.25"$  (6 mm).

Max. flow rates are at 60 psi (414 kPa).

WaterSense® is a registered trademark of the U.S. Environmental Protection Agency.

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. See current full-line price book for finish options and product availability.

Masco Canada Limited  
350 South Edgeware Rd, St Thomas, Ontario, Canada N5P 4L1  
1-800-387-8277


**620TPA3328TR**

This spec was produced on April 12, 2024.



Hardwire Operated - Single Hole Deck Mount  
Gooseneck Faucet - Recessed Control Box

# 620TPA3328TR



**NOTICE** Dimensions are for reference only. Measurements may vary  $\pm 0.25"$  (6 mm).

Max. flow rates are at 60 psi (414 kPa).

**WaterSense**® is a registered trademark of the U.S. Environmental Protection Agency.

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. See current full-line price book for finish options and product availability.

Masco Canada Limited  
350 South Edgeware Rd, St Thomas, Ontario, Canada N5P 4L1  
1-800-387-8277

**620TPA3328TR**

This spec was produced on April 12, 2024.