



Model Number	kW	Max. Cu. Ft. Range	Volts	Phase	Amps	Breaker Size
5COM30-PAC-630-240-03			240	3	72	90
5COM30-PAC-630-208-03	30	1250	208	3	84	110
5COM30-PAC-630-480-03			480	3	36	45
5COM36-PAC-636-240-03			240	3	87	110
5COM36-PAC-636-208-03	36	1500	208	3	100	125
5COM36-PAC-636-480-03			480	3	44	60
5COM48-PAC-648-240-03			240	3	116	150
5COM48-PAC-648-208-03	48	2000	208	3	133	175
5COM48-PAC-648-480-03			480	3	58	80

WARRANTY

- Steam Generators Lifetime limited warranty; or for commercial purchasers (including for steam bath generators with model numbers beginning with 5COM, which are intended solely for heavy commercial use), one (1) year from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Electronic Parts for Steam Bath Generators, Controls, Spa Options and Accessories two (2) years from the date the product is received by the original consumer purchaser or their authorized representative (installation contractor, etc.); or for commercial purchasers, one (1) year from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



see what Delta can do

COMMERCIAL STEAM GENERATOR

- 30KW (5COM30)
- 36KW (5COM36)
- 48KW (5COM48)

FEATURES:

- Automatic Regulator Pressure Control
- · High Limit Pressure Control with Manual Reset
- Pressure Gauge
- Sight Glass Gauge
- Check Valves
- Drain Valve
- · Silicone Steam Head Cover
- · Low Water safety cut-off to deenergize the heater in the event of a low water condition
- Automatic Microprocessor controlled water feed with stainless steel probes

STANDARD SPECIFICATIONS:

- Dimensions: 35" L x 21" W x 27" H
- Generator Shipping Weight: 5COM9 thru 24 200lb and 5COM30 thru 48 300lb
- Operating Pressure: Max. 15 PSI
- Water Feed: 1/2" NPT
- Steam Output: 3/4" NPT
- Commercial generators are designed to support round the clock operation
- Can program 2 steam rooms with one control when paired with 5COM-CN-010CR Second Room Package

OPTIONAL EQUIPMENT

5COM-CN-010CR - Second Room Package

5COM-GA-014-208 - Automatic Blowdown Valve - 208V 5COM-GA-015-240 - Automatic Blowdown Valve -

480/240V

5COM-CN-016CS - TA-100 Temperature Alert

5COM-SP-MU-50 - Commercial Aroma Pump

5COM-SP-018-50 - Eucalyptus Aromatherapy Pure Oil - 1.1 liter bottle

5COM-GA-006 - Commercial Stand

5COM-GA-007 - ASME Blowdown Tank

5COM-GA-020 - Aux Cutoff Control

5COM-GA-021 - Blowdown Tempering Valve

COMPLIES WITH:

- ASME BPVC Section I
- UL Listed