

Electronic Showers

Hardwire Operated (860T1) - Push button electronic shower system

Model No: 860T107

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- Lindicates compliance to ICC/ANSI A117.1
- Control/Sensor Box Option 7, Pressure Balancing Valve, complies with ASSE 1016/ASME A112.1016/CSAB125.16
- Control/Sensor Box Option 8, Thermostatic Mixing Valve certified to CSA B.125.3. Complies with ASSE 1069 and ASSE 1070/ASME A112.1070/ CSA B125.70.
- Handshower back flow protection provided by two integral certified check valves in series, which operate independently, ASME A112.18.3
- Patented
- (Contact Delta Representative for State and/or Local Approvals)





NOTES:

Supplied as COMPLETE PRODUCT ONLY

SPECIFICATION:


- Push button electronic shower system
- Hardwire 24 VAC to 6 VDC or Battery 4 "AA" 6 VDC
- Stainless steel cover with S/S vandal resistant mounting screws
- Metal mounting box
- Field adjustable shower time
- Slow closing solenoid valve
- Integral stop
- Tempered water supplied to solenoid valve (except control box options No. 3 and 6)
- Hardwire Operated (860T1) Push button electronic shower system
- No fixed shower outlet supplied
- Tempered water supplied to solenoid valve
- Models supplied without a showerhead must be used with showerheads rated at 4.5 L/min @ 310 kPa (1.2 gpm @ 45 psi) or higher.

OPERATION:

- Shower flows when push button is activated.
- Adjustable maximum continuous run time
- 10 minutes.
- Factory set to 3 minutes.

(Dimensional drawing on following page)





Delta reserves the right (1) to make changes to specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference. Measurement may vary plus or minus 6mm(0.25"). Mounting locations are suggested only. Check with local codes for requirements in your area. This spec was produced May 06, 2021.