

Specific Features:

Submitted Model No.:_____

9 5/16" (237 mm) 13 7/8" (352 mm) 3 1/4" (83 mm) 2 3/8 " (60 mm) 2 7/16" (62 mm) 7 3/16" (182 mm) 7 1/8" (181 mm) 5 13/16" (147 mm) 2 1/2" (64 mm) 6 7/8" (175 mm) 2 1/8 " (53 mm) 2 13/16" (71 mm) 2 1/8" (53 mm) 5 1/2" (140 mm) 10 3/8" (263 mm) 1 1/6 " Dia. (27 mm) (102 mm) Min.

ODELTA

KITCHEN FAUCETS

- Leland[™] Collection
- Single Handle Deck Mount
- 2-Function Pull-Down
- 2 or 3 Hole Sink Applications
- Optional Soap Dispenser
- Quick Snap® Hose Installation

STANDARD SPECIFICATIONS:

- Single handle, 2-function pull-down kitchen faucets for exposed mounting on two and three hole sinks.
- Solid brass fabricated body.
- 13 7/8" (352 mm) high, 9 5/16" (237 mm) long, spout swings 360°.
- Lever handle. Control mechanism is rotating stainless steel ball type with replaceable non-metallic seats operating in stainless steel lined sockets.
- Control shall return to neutral position when faucet is turned off.
- Quick Snap® connect hoses.
- Pull-down wand operates in an aerated or spray mode via a twist activated diverter.
- Red/blue graphics on handle button to indicate hot/cold temperature.
- Twist and lock mechanism eliminates spray head wobble.
- Integral double check valves in sprayer assembly.
- Disposable hose lead to aid installation.
- Mounting wrench to assist in tightening mounting nut securely.
- Hose travels inside mounting shank so it will not interfere with deck edges.
- Recommended hole size 1 3/8" (35mm) on 4" (102mm) centers.

WARRANTY

- Lifetime Faucet and Finish Limited Warranty to the original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all industrial, commercial and business applications.

COMPLIES WITH:

ASME A112.18.1 / CSA B125.1 Indicates ADA compliance to ICC/ANSI A117.1/ADA







