
Submitted Model No.:_	
Specific Features:	



▲ Designate proper finish suffix

Your Delta Faucet handshower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.



see what Delta can do

HAND SHOWER

- H20kinetic® Hand Shower
- Wall Mount or Shower Arm Mount
- Certified Dual Check Valves

FEATURES:

- Lumicoat[™] Finish (-PR models only)
- Lumicoat[™] Finishes easily wipe clean without cleaners and chemicals on the products most commonly touched areas

STANDARD SPECIFICATIONS:

- Maximum 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- Hand held shower with one setting
- Adjustable wall mount (55421) for hands-free showering
 60"-82" (1524 mm 2083 mm) metal stretchable hose (55421)
- Spray face rotates 360°

WARRANTY

- Parts and Finish Lifetime limited warranty: or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1 ◆
- ASME A112.18.3
- EPA WaterSense®