To reduce the amount of lead in your drinking water, allow the water to run for a moment before filling your glass and remember to always use cold water for drinking purposes.	To reduce the amount of lead in your filling your glass and remember to al		
<b>CONSUMER PROTECTION WARNING</b> Under the Safe Drinking Water Act, the U.S. Environmental Protection Agency restricts the amount of lead used in brass and solder. Your new faucet is made in strict compliance with all government standards. The materials used in the manufacture of this faucet are of industry standard quality and are similar to other plumbing products having brass fittings.	Under the Safe Drinking Water Act, t amount of lead used in brass and so all government standards. The mate standard quality and are similar to of	ith safety glasses.	<ul> <li>ALWAYS protect your eyes with safety glasses.</li> </ul>
		PS	SAFETY TIPS
new by cleaning it periodically with a sort cioth. Avoid abrasive cleaners, steel wool and harsh chemicals that will dull the finish and void your warranty. Brass finishes are polished, then protected with a lacquer coating to help prevent tarnishing. Clean these surfaces only with a damp, soft cloth.	new by cleaning it periodically with a sort cor that will dull the finish and void your warranty Brass finishes are polished, then protected v surfaces only with a damp, soft cloth.	ector nuts, then use one wrench to one additional turn. Connections that	<ul> <li>When installing your new faucet, hand tighten the connector nuts, then use one wrench to anchor the fitting and a second wrench to tighten the nut one additional turn. Connections that are too tight will reduce the integrity of the system.</li> </ul>
Your new Design House faucet is designed to give you years of trouble free performance. Keep it looking	Your new Design House faucet is designed t	DINTS	IMPORTANT POINTS
MAINTENANCE	м	● raucet subply tubes	• (z) crescent wrenches
		<ul> <li>silicon sealer</li> <li>flashlight</li> </ul>	basin wrench     Teflon tape     concenter
4G, 4H are not included).		this faucet:	Helpful tools to install this faucet:
		ble free performance. Thank you for nese instructions carefully before	Your new Design House faucet will give you years of trouble free performance. Thank you for choosing our product for your home. <b>Please read all of these instructions carefully before installing your new faucet.</b>
(3D) facing the wall. Note: Air gap to be installed that the flood level mark (F/L) shall be at or ther receptacle thood level of the sink or other receptacle which may be connected to the sanitary drain into which the air gap discharges.			
4 3.Thread ribbed nut (3A) fully onto body. Tighten nut (3B) firmly. Snap cap (3C) onto ribbed nut, with the slotted vents			
			Models 522946, 522953, 522961, 522979
	2.Insert air gap (2A) through sink deck hole, leaving approximately 1/2 " of the body threads showing above sink deck. (Back the nut (2B) down if necessary).		AIR GAP
	1.Remove cap (1A) and ribbed nut (1B).	Mequon, WI 53092 1-800-558-8700	
		brand of DHI Corp.	
INSTALLATION PROCEDURE	INSTALL	Design House is a registered	