



Project: Date:

Prepared by:

Comments:



FEATURES

- 5 Year Warranty
- Direct **65W** Incandescent Replacement
- **No Housing Required!!!**
- Energy Savings of up to 80%
- Lumen Maintenance over 70% @ 50,000+ Hours
- Compatible w/Most Triac Phase-Control Dimmers
- No UV/IR Radiation, No Toxic Mercury
- Die-Cast Aluminum Housing

OPTICS

- Frosted White Lens
- Baffle Reflector

APPLICATIONS

- Ceiling Installations for General Ambient Lighting in Homes, Offices & Public Facilities
- Retail Store Lighting
- Museums, Galleries, Showrooms
- Hotels, Hospitality Areas
- Hospitals, Clinics, Workrooms
- Corridors, Lobbies, Stairways

CERTIFICATIONS

- cETLus Listed
- Energy Star Listed for Rebate and Tax Incentive Programs
- California Title 24 Compliant
- Rated for Wet-Locations / Airtight Rated

MODEL NUMBER	KELVIN (CCT)	WATTS	LUMENS	CRI	TRIM COLOR
EV407943WH30	3000K	11.15	725	91	WHITE
EV407943WH40	4000K	11.15	790	91	WHITE

SPECIFICATIONS

Warranty:	5 yrs	Max. Ambient Temp:	45° C	R9-Value:	57	Beam Angle:	102°
Expected Life:	50,000 hrs	Min. Ambient Temp:	-18° C	Power Factor:	>0.9	THD:	<20%





Project: Date:

Prepared by:

Comments:

DIMMING COMPATIBILITY

February 27, 2017		407943 Triac/Phase-cut dimmers									
Brand	Type	Series	Model #	Wiring	watts	dimming method	Version Code	Max # of Luminaires	Notes		minimum dimming range
Lutron	C.L	Aniadni/Toggler C.L	AYCL-153P	Single-pole/3-way	150	Toggler	TB, T9	13	3-Way only works with a 3-Way switch		3%
			TGCL-153P								
		Diva C.L	DVCL-153P								
		SkyLark C.L	SCL-153P								
		SkyLark Contour C.L	CTCL-153P								
		Lumea C.L	LGCL-153P								
	Maestro C.L	MACL-153M	Single-pole/3-way/multi-location	150	Digital	2014	13	3-Way only works with a 3-Way switch or dimmer companion MA-R (not a dimmer). Multi-location only work with MA-R	4%		
		MSCL-VP153M	Single-pole/3-way/multi-location	150	Digital/Vacancy Sensor	T2	13	3-Way only works with a 3-Way switch or dimmer companion MA-R (not a dimmer). Multi-location only work with MA-R	4%		
		MSCL-OP153M	Single-pole/3-way/multi-location	150	Digital/Occupancy Sensor						
		MRF2-6CL	Single-pole/3-way/multi-location	150	Digital and Wireless	M6	13	3-Way or multi-location only works with companion MA-R (not a dimmer)	4%		
		Nova T	NTCL-250	Single-pole	250	slide to off	BR Y02	22		4%	
		Grafik T	GT-150	Single-pole/3-way/multi-location	150	Digital	T6	13	3-Way or multi-location only works with companion GT-AD (not a dimmer)	3%	
RF C.L	Grafik T RF	GTJ 150	Single-pole/3-way/multi-location	150	Digital	M6	13	3-Way or multi-location only works with companion GT-AD (not a dimmer)	3%		
	Wireless	Caseta	PD-6WCL	Single-pole or multi-location	150	Digital and Wireless	SD11	13	Multi-location only works with Pico wireless remote PJ2	0%	
Leviton	Universal Dimmer	Decora	DSL06-1L	Single-pole/3-Way	300	slide with ON/OFF button	NA	27	3-Way only works with a 3-Way switch	24%	
		Illuma Tech	IFL06-10	Single-pole/3-Way	150	slide with ON/OFF button	NA	13	3-Way only works with a 3-Way switch	4%	
		Sureslide	6672-1L	single	150	slide to off	NA	13		12%	
		Sureslide	6674-PO	Single-pole/3-Way	150	slide with ON/OFF button	NA	13	3-Way only works with a 3-Way switch	4%	
		Renu	REL06	Single-pole/3-Way	300	Digital	NA	27	3-Way only works with remote RE00R <i>Requires neutral wire connection</i>	0%	
		Decora Digital	DDMX1-BL	Single-pole/3-Way	450	Digital or Bluetooth	NA	41	3-Way only works with remote DDOOR-DL <i>Requires neutral wire connection</i>	0%	

