

Rain shower for recessed ceiling installation 300 x 240 mm

28 043 980



Fits: IMO, LULU, MEM, SYMETRICS, CL.1, CYO

- rain shower 300 x 240mm
- Rain flow, max. flow rate 6,8 l/min
- Spray flow, max. flow rate 6,8 l/min
- min. recess depth 137,5 mm
- with anti-scale system
- This product reduces water consumption by % (compared to requirements of EPAct '92)
 This product can contribute to Water Use
- Reduction in LEED® Green Building Rating
- Not suitable for use in a steam bath

Three-way diverter ensures that the product does not exceed the max. flow rate of 2.5 gpm at any setting. It does not permit the use of two functions simultaneously.

Three-way diverter trim is sold separately

Three-way diverter ensures that the product does not exceed the max. flow rate of 2.5 gpm at any setting. It does not permit the use of two functions simultaneously.

Three-way diverter trim is sold separately

Chrome	28 043 980-00 0010
Brushed Platinum	28 043 980-06 0010
Platinum	28 043 980-08 0010
Matte White	28 043 980-10 0010
Brushed Durabrass (23kt Gold)	28 043 980-28 0010
Matte Black	28 043 980-33 0010
Brushed Champagne (22kt Gold)	28 043 980-46 0010
Champagne (22kt Gold)	28 043 980-47 0010
Brushed Chrome	28 043 980-93 0010
Brushed Dark Platinum	28 043 980-99 0010

Required miscellaneous



Concealed ceiling installation box for recessed ceiling installation

x 35 043 970-90

•recess depth 137mm





Rain shower for recessed ceiling installation 300 x 240 mm

28 043 980


mm [inches]







Flow rate chart



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	90 17 20 260 00 90	flange	1	2
2	90 24 03 309 02 90	connection	1	2