DURAVIT

Happy D.2 Wall Mounted Toilet # 222209..92 / 222209..92 / 222209..92

540 21 1/4

|< 14 3/8 " >|

	400	$2^{\frac{03}{1/2}} + \frac{2^{\frac{03}{10}}}{2^{\frac{055}{10}}} + \frac{2^{\frac{055}{10}}}{2^{\frac{010}{10}}}$	313 133/4* 133/4* 133/4* 133/4* 133/4* 123/8* 123/8* 123/8* 123/8* 123/8* 123/8* 123/8* 123/4* 1
Wall Mounted Toilet	Dimension	Weight	Order number
Flush water quantity: 1.2/0.8 gal, Washdown model, Flushing rim: Rimless, Flush system: washdown model, Outlet horizontal, Concealed fixation, ADA: Yes, cUPC listed: Yes			
Colors			
00 White 20 HygieneGlaze (an antibacterial ceramic glaze that provides almost indefinite effectiveness) 89 Anthracite/Anthracite Matte			
Variant			
White High Gloss, Flush water quantity: 1.2/1.28 gal, WaterSense: Yes		54.454 lb	22220992
White High Gloss, HygieneGlaze, WaterSense: Yes		54.454 lb	22220992
Interior color Anthracite High Gloss, Exterior color Anthracite Matte, WaterSense: Yes		54.454 lb	22220992
Spare parts			
Noise reduction gasket		0.441 lb	005090
Suitable products			
Toilet Seat Shape: Rectangular, Slow close: Yes, Removable Seat, Hinge material: Stainless Steel, 14 1/8 x 16 7/8 "	14 1/8 x 16 7/8	, u	006459
Actuator Plate Actuator plates ,			115770
Actuator Plate A1 Plastic, Dual Flush, Trip lever type: Mechanical, Flush operation technology: Manual, Installation Type: surface mounted, Includes mounting frame, including mounting kit, Includes push rod, 8 1/2 x 3/8 "	8 1/2 x 3/8 "		WD5008
In-Wall Tank & Carrier Standard Includes HDPE toilet wall- mounted outlet bend DN 90/90, Powder-coated, Installation Type: In lightweight stand construction, Installation Type: Drywall, Max. projection toilet: 24 5/8 ", Adjustable height: 9 1/ ", Trip lever type: Mechanical, Trip lever placement: Front, Adjustable flush volumes, Flush type: Dual Flush, Insulated tank, Self-supporting, Suitable for panelling with plasterboards 23 1/4 x 3 1/2 "			WD1022

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are nonbinding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.