




Starck 3 Wall Mounted Toilet # 222709..92 / 222709..92

| < 14 3/4 " > |



Wall Mounted Toilet	Dimension	Weight	Order number
Washdown model, Flushing rim: Closed, Flush system: washdown model, Outlet horizontal, Fixing Included: Durafix, cUPC listed: Yes			
Colors			
00 White High Gloss 20 White High Gloss, HygieneGlaze			
Variant			
White High Gloss, Flush water quantity: 1.6/0.8 gpf, WaterSense: Yes, ADA: Yes	14 3/4 "x19 1/8 "	52.911 lb	222709..92
White High Gloss, HygieneGlaze, Flush water quantity: 1.6/0.8 gpf, WaterSense: Yes, ADA: Yes	14 3/4 "x19 1/8 "	52.911 lb	222709..92
Accessory			
Noise reduction gasket	16 1/2 x 15 3/8 "	0.441 lb	005090
Suitable products			
Toilet Seat Slow close: Yes, Removable Seat, Hinge material: Stainless Steel, 14 5/8 x 17 "	14 5/8 x 17 "		006389
Actuator Plate A1 Plastic, Dual Flush, Trip lever type: Mechanical, Flush operation technology: Manual, Installation Type: surface mounted, Includes mounting frame, including mounting kit, Includes push rod, 3/8 x 8 1/2 "	3/8 x 8 1/2 "		WD5008
In-Wall Tank & Carrier Standard Includes HDPE toilet wall-mounted outlet bend DN 90/90, Powder-coated, Installation Type: In lightweight stand construction, Installation Type: Drywall, Max. projection toilet: 24 5/8 ", Adjustable height: 9 1/2 ", Trip lever type: Mechanical, Trip lever placement: Front, Adjustable flush volumes, Flush type: Dual Flush, Insulated tank, Self-supporting, Suitable for panelling with plasterboards, 3 1/2 x 23 1/4 "	3 1/2 x 23 1/4 "		WD1022

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.