

**FODURAVIT** 





Mirror cabinet	Dimension	Weight	Order number
built-in version, Standard-Version, cEGS/IAPMO®*, 2 mirror doors, 2 glass shelves, external switch, built-in only in combination with built-in set, LED (life span > 30,000 hours), LED module permanently enclosed, Mirrors cabinets require a GFCI 110 V 60 Hz power source and are hardwired to a circuit provided by the customer. , LED module 4000 kelvin light color 11 Watt	,		
Colors			
M00			
Variant			
	31 7/8" x 5 7/8" Inch		LM782100000
Infobox			
# LM 7821 and LM 7822 are available from stock, On/off function set please see page XXX, * Complies with following standards: Les specification for ordering:, - built-in yes / no			
Cortable and desta			
Suitable products	2 1/211 la ab		111/0700
Magnetic strip in stainless steel , 3 1/2" Inch	3 1/2" Inch		UV9709
Recess frame for LM mirror cabinet Built-in frame: recess mounting frame in MDF White, width = X, height = 31"; recess mounting frame in White Aluminum, width = X, height = 32"; frame strength = 1", 33 $7/8$ " x 5 $1/2$ " Inch	33 7/8" x 5 1/2" Inch		LM9876

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.