

Project name:

Fixture type:

Date:

6" Super Sloped Ceiling Medium Base IC Airtight Remodel Housing

ELCO Slant allows for installation in sloped ceilings ranging from 7/12 (30°) to 12/12 (45°). Can be used in insulated ceilings. Fits in 2" x 8" joist construction.



Features

- Airtight aluminum Single Wall Construction.
- Integral thermal protector guards against improper lamping.
- Designed for use in 7/12 to 12/12 sloped ceiling.
- Socket: Medium base E26.
- Compatible with Medium Base Incandescent, CFL or LED Lamp MAX. 75W. Works with LED Quick-Connect Inserts with PSA30 Socket Adapter.

Technical Details

Construction:

- IC Rated for Direct Contact with Insulation.
- Designed for use in 7/12 to 12/12 sloped ceiling.
- Aluminum housing for greater heat dissipation.

Installation: Designed for ceiling plenums where 2x8 joists or taller are used. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts and One 3/4" knockout. Four true pry-out knockout slots for easy Romex installation.

Electrical:

- Rated for 120V or 277V input.
- For 277V step down to 120V housing consult factory.

Trims: Compatible with EL602, EL603, EL604, EL606, EL607, EL608.

Listings: UL Listed for Damp Location.

UL Listed for Direct Contact with Insulation and Combustible Material.


UL Listed for Feed Through.

Meets restricted air flow requirements (Per ASTM E-283 Standard).

Specifications

Wattage	75W			
Voltage	120V			
Lamp Type	Medium Base (E26)			
Damp Location Listed				

Dimensions



Product Number

:				
See installation sheet for	Item	Lamp type	Watts	Voltage
	EL901RICA	Medium Base (E26)	75W	120V
ade size conduit knockouts and n.				