

6" Remodel Frame with Driver




Features

- Optional 90 minutes, 120/277 VAC, 60Hz Emergency Backup.
- USA designed and assembled.
- LED Light Engine sold separately (see Compatible Trims).

Specifications

Lumens	850 lm - 6000 lm
Voltage	120/277V or 120V
Dimmable	Triac/ELV/0-10V, Sunset, Lutron
Power Factor	≥0.9
Damp Location	Listed

Dimensions



Technical Details

Construction:

Constructed from 16 gauge galvanized steel for commercial building applications.

Installation:

Remodel clips hold housing sturdily into place.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts and four pry-out knockout slots for easy romex installation.

Electrical:

- Driver is rated for 120V and 277V input (120/277V).
- High Efficiency driver with a power factor > 0.9.
- Can be specified with Lutron drivers for specific applications.

Dimmability:

- 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver.
- 0-10V dimming down to 51% with a compatible dimmer.
- Flicker-Free Dimming.
- Can be specified with Lutron drivers for 0.1% and 1% dimming.
- For a full list of dimmers refer to the Dimmer Compatibility List.

Listings: cULus Listed for Damp Location. cULus Listed for Wet Location with select trims. cULus Listed for Direct Contact with Insulation and Combustible Material for units up to 2000 lm. cULus Listed for Feed Through. ENERGY STAR® Certified.

Warranty: ELCO Products are built to last. 5-year Limited warranty.

Product Numbers

Item	Lumens	Voltage	Dimming
E6LRU08D	850 lm	120/277V	Triac/ELV/0-10V
E6LRU08S	850 lm	120/277V	Sunset
E6LRU08L	850 lm	120V	Lutron
E6LRU12D	1250 lm	120/277V	Triac/ELV/0-10V
E6LRU12S	1250 lm	120/277V	Sunset
E6LRU12L	1250 lm	120V	Lutron
E6LRU16D	1600 lm	120/277V	Triac/ELV/0-10V
E6LRU16S	1600 lm	120/277V	Sunset
E6LRU16L	1600 lm	120V	Lutron
E6LRU20D	2000 lm	120/277V	Triac/ELV/0-10V
E6LRU20S	2000 lm	120/277V	Sunset
E6LRU20L	2000 lm	120V	Lutron
E6LRU30D	3000 lm	120/277V	Triac/ELV/0-10V
E6LRU30S	3000 lm	120/277V	Sunset
E6LRU30L	3000 lm	120V	Lutron
E6LRU40D	4000 lm	120/277V	Triac/ELV/0-10V
E6LRU40L	4000 lm	120V	Lutron
E6LRU60D	6000 lm	120/277V	Triac/ELV/0-10V
E6LRU60L	6000 lm	120V	Lutron

Product Number Builder


Example: **E6LRU08D**

ELCO Laurel 6" Remodel Frame	Voltage	Lumens	Dimming	Optional
<input type="text" value="E6LR"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	U 120/277V	08 850 lm 12 1250 lm 16 1600 lm 20 2000 lm 30 3000 lm 40 4000 lm 60 6000 lm	D Triac/ELV/0-10V S Sunset L Lutron	(blank) No EM EM1 8W Emer. Backup EM2 12W Emer. Backup


Compatible Products

For use with 6" Laurel™ Frames


6" Laurel™ Commercial LED Light Engines




E610L
Reflector Trim



E611L
Wall Wash Trim



E612L
Drop Glass Trim



E618L
Adjustable Trim

PRODUCT NUMBER BUILDER

Laurel™ Trim		Lumen		Color Temperature		Finish		Beam Angle	
<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>	
E610L	Reflector	08	850 lm	27	2700K	H	All Haze	(blank)	60°
E611L	Wall Wash	12	1250 lm	30	3000K	W	All White	-F	36°
E612L	Drop Glass	16	1600 lm	35	3500K	B	All Black	-N	25°
E618L	Adjustable	20	2000lm	40	4000K	C	All Chrome	-S	10°
		30	3000lm	SD	Sunset Dimming	HW	Haze w/White Ring		
		40	4000lm						
		60	6000lm						