

9" LED Retrofit Kit with Driver




Features

- Optional 90 minutes, 120/277 VAC, 60Hz Emergency Backup.
- USA designed and assembled.
- LED Light Engine sold separately (see Compatible Trims).

Specifications

Lumens	850 lm - 6000 lm
Voltage	120/277V
Dimmable	Triac/ELV/0-10V, Sunset, Lutron EcoSystem
Power Factor	≥0.9
Damp Location	Listed

Dimensions



Technical Details

Installation:

Designed to be installed in existing holes for retrofitting less efficient lighting technologies. Junction box is mounted with driver and can be mounted into the ceiling with flex going from power to junction box and from junction box to light engine.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts.

Electrical:

- Driver is rated for 120V and 277V input (120/277V).
- High Efficiency driver with a power factor > 0.9.
- Can be specified with Lutron drivers for specific applications.

Dimmability:

- 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver.
- 0-10V dimming down to 5% with a compatible dimmer.
- Flicker-Free Dimming.
- Can be specified with Lutron drivers for 0.1% and 1% dimming.
- For a full list of dimmers refer to the Dimmer Compatibility List.

Listings: UL Listed for Damp Location. UL Listed for Wet Location with select trims. UL Listed for Direct Contact with Insulation and Combustible Material for units up to 2000 lm. UL Listed for Feed Through. ENERGY STAR® Certified.

Warranty: ELCO Products are built to last. 5-year Limited warranty.

Product Numbers

Item	Lumens	Voltage	Dimming
E9LTU08D	850 lm	120/277V	Triac/ELV/0-10V
E9LTU08S	850 lm	120/277V	Sunset
E9LTU08L	850 lm	120/277V	Lutron EcoSystem
E9LTU12D	1250 lm	120/277V	Triac/ELV/0-10V
E9LTU12S	1250 lm	120/277V	Sunset
E9LTU12L	1250 lm	120/277V	Lutron EcoSystem
E9LTU16D	1600 lm	120/277V	Triac/ELV/0-10V
E9LTU16S	1600 lm	120/277V	Sunset
E9LTU16L	1600 lm	120/277V	Lutron EcoSystem
E9LTU20D	2000 lm	120/277V	Triac/ELV/0-10V
E9LTU20S	2000 lm	120/277V	Sunset
E9LTU20L	2000 lm	120/277V	Lutron EcoSystem
E9LTU30D	3000 lm	120/277V	Triac/ELV/0-10V
E9LTU30S	3000 lm	120/277V	Sunset
E9LTU30L	3000 lm	120/277V	Lutron EcoSystem
E9LTU40D	4000 lm	120/277V	Triac/ELV/0-10V
E9LTU40L	4000 lm	120/277V	Lutron EcoSystem
E9LTU60D	6000 lm	120/277V	Triac/ELV/0-10V
E9LTU60L	6000 lm	120/277V	Lutron EcoSystem


Product Number Builder

Example: **E9LTU08D**

ELCO Laurel 9" Retrofit Kit	Voltage	Lumens	Dimming	Optional
E9LT	U 120/277V	08 850 lm 12 1250 lm 16 1600 lm 20 2000 lm 30 3000 lm 40 4000 lm 60 6000 lm	D Triac/ELV/0-10V S Sunset L Lutron	No EM EM1 8W Emer. Backup EM2 12W Emer. Backup

For use with 9" Laurel™ Frames

9" Laurel™ Commercial LED Light Engines



E910L
Reflector Trim

PRODUCT NUMBER BUILDER

Laurel™ Trim	Lumen	Color Temperature	Finish	Beam Angle
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
E910L Reflector	08 850 lm	27 2700K	H All Haze	(blank) 60°
	12 1250 lm	30 3000K	W All White	-F 36°
	16 1600 lm	35 3500K	B All Black	-N 25°
	20 2000lm	40 4000K	C All Chrome	-S 10°
	30 3000lm	SD Sunset Dimming	HW Haze w/White Ring	
	40 4000lm			
	60 6000lm			