



Single Circuit




Single Circuit Track

Track supplied with dead end and mounting hardware




Live End Connector

Live end connector used for direct wiring



Flexible Connector

Flexible connector to join two track sections at an angle up to 90°. Can be used as a feed point



Straight Connector

Power feedable connector to join two track sections

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
|---------|----------------|

| | |
|---------|-------------|
| EP002W | White / 2' |
| EP004W | White / 4' |
| EP006W | White / 6' |
| EP008W | White / 8' |
| EP012W | White / 12' |
| EP002B | Black / 2' |
| EP004B | Black / 4' |
| EP006B | Black / 6' |
| EP008B | Black / 8' |
| EP0012B | Black / 12' |
| EP002BZ | Bronze / 2' |
| EP004BZ | Bronze / 4' |
| EP006BZ | Bronze / 6' |
| EP008BZ | Bronze / 8' |
| EP002N | Nickel / 2' |
| EP004N | Nickel / 4' |
| EP006N | Nickel / 6' |
| EP008N | Nickel / 8' |

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
|---------|----------------|


| | |
|---------|--------|
| EP801W | White |
| EP801B | Black |
| EP801BZ | Bronze |
| EP801N | Nickel |

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
|---------|----------------|

| | |
|---------|--------|
| EP802W | White |
| EP802B | Black |
| EP802BZ | Bronze |
| EP802N | Nickel |


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
|---------|----------------|

| | |
|---------|--------|
| EP803W | White |
| EP803B | Black |
| EP803BZ | Bronze |
| EP803N | Nickel |




L Connector

Power feedable connector to join two track sections at a 90° angle



T Connector

Power feedable connector to join three track sections



X Connector

Power feedable connector to join four track sections

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
|---------|----------------|


| | |
|---------|--------|
| EP804W | White |
| EP804B | Black |
| EP804BZ | Bronze |
| EP804N | Nickel |

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
|---------|----------------|

| | |
|---------|--------|
| EP805W | White |
| EP805B | Black |
| EP805BZ | Bronze |
| EP805N | Nickel |


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
|---------|----------------|

| | |
|---------|--------|
| EP806W | White |
| EP806B | Black |
| EP806BZ | Bronze |
| EP806N | Nickel |




Mini Connector

Mini Connector to join two track sections. Cannot be used as a feed point




Floating Canopy

Can be used anywhere along length of track to supply power. Includes end cap



End Feed Kit

Kit includes live end feed and canopy to mount on outlet box. 4 1/2" x 4 1/2" x 1/4" thick



Dead End

Dead end cap for single and double circuit track

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
|---------|----------------|

| | |
|---------|--------|
| EP808W | White |
| EP808B | Black |
| EP808BZ | Bronze |
| EP808N | Nickel |

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
|---------|----------------|

| | |
|---------|--------|
| EP809W | White |
| EP809B | Black |
| EP809BZ | Bronze |
| EP809N | Nickel |


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
|---------|----------------|

| | |
|---------|--------|
| EP810W | White |
| EP810B | Black |
| EP810BZ | Bronze |
| EP810N | Nickel |

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
|---------|----------------|

| | |
|---------|--------|
| EP812W | White |
| EP812B | Black |
| EP812BZ | Bronze |
| EP812N | Nickel |


Single Circuit



T-Bar Ceiling Feed

Live feed with outlet box for use with T-bar ceilings

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP817W | White |
| EP817B | Black |
| EP817BZ | Bronze |
| EP817N | Nickel |



Dead Mini Connector

Dead Mini Connector to join two track sections without passing the power


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP825W | White |
| EP825B | Black |
| EP825BZ | Bronze |
| EP825N | Nickel |



T-Bar Ceiling Feed

In-line T-bar ceiling feed


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP827W | White |
| EP827B | Black |



Cord and Plug Connector

Cord and Plug Connector for single circuit track. 10 Amp MAX or 1200W. 12 ft. long


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP850W | White |
| EP850B | Black |
| EP850BZ | Bronze |
| EP850N | Nickel |



Conduit Connector

To start a surface run


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP880W | White |
| EP880B | Black |
| EP880BZ | Bronze |
| EP880N | Nickel |



Conduit Continuation Kit

Kit includes: (1) Left and (1) Right feed, to continue around obstructions with 1/2" surface conduit


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP979W | White |
| EP979B | Black |



Live Feed with Current Limiter

Current Limiter for single circuit track. 1A to 12A available

| CAT NO. | SPECIFICATIONS |
|-------------|------------------|
| EP840W-1A | White \ 1 Amp |
| EP840W-2A | White \ 2.5 Amp |
| EP840W-5A | White \ 5 Amp |
| EP840W-7A | White \ 7.5 Amp |
| EP840W-10A | White \ 10 Amp |
| EP840W-12A | White \ 12 Amp |
| EP840B-1A | Black \ 1 Amp |
| EP840B-2A | Black \ 2.5 Amp |
| EP840B-5A | Black \ 5 Amp |
| EP840B-7A | Black \ 7.5 Amp |
| EP840B-10A | Black \ 10 Amp |
| EP840B-12A | Black \ 12 Amp |
| EP840BZ-1A | Bronze \ 1 Amp |
| EP840BZ-2A | Bronze \ 2.5 Amp |
| EP840BZ-5A | Bronze \ 5 Amp |
| EP840BZ-7A | Bronze \ 7.5 Amp |
| EP840BZ-10A | Bronze \ 10 Amp |
| EP840BZ-12A | Bronze \ 12 Amp |




In-Line Feed Connector with Current Limiter

Current Limiter for single circuit track. 1A to 12A available

| CAT NO. | SPECIFICATIONS |
|------------|-----------------|
| EP841W-1A | White \ 1 Amp |
| EP841W-2A | White \ 2.5 Amp |
| EP841W-5A | White \ 5 Amp |
| EP841W-7A | White \ 7.5 Amp |
| EP841W-10A | White \ 10 Amp |
| EP841W-12A | White \ 12 Amp |
| EP841B-1A | Black \ 1 Amp |
| EP841B-2A | Black \ 2.5 Amp |
| EP841B-5A | Black \ 5 Amp |
| EP841B-7A | Black \ 7.5 Amp |
| EP841B-10A | Black \ 10 Amp |
| EP841B-12A | Black \ 12 Amp |


Two Circuit



Two Circuit Track

Track supplied with dead end and mounting hardware


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC002W | White / 2' |
| EC004W | White / 4' |
| EC006W | White / 6' |
| EC008W | White / 8' |
| EC012W | White / 12' |
| EC002B | Black / 2' |
| EC004B | Black / 4' |
| EC006B | Black / 6' |
| EC008B | Black / 8' |
| EC012B | Black / 12' |



Live End Connector

2-Circuit live end connector to start a run


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC801W | White |
| EC801B | Black |



L Connector

Power feedable connector to join two track sections at a 90° angle


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC804W | White |
| EC804B | Black |



Flexible Connector

Flexible connector to join two track sections at an angle up to 90°


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC802W | White |
| EC802B | Black |



T Connector

Power feedable connector to join three track sections


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC805W | White |
| EC805B | Black |



Straight Connector

Power feedable connector to join two track sections


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC803W | White |
| EC803B | Black |



X Connector

Power feedable connector to join four track sections


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC806W | White |
| EC806B | Black |



Mini Connector

Mini Connector to join two track sections. Cannot be used as a feed point


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC808W | White |
| EC808B | Black |



Floating Canopy

Can be used anywhere along length of track to supply power. Includes end cap


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC809W | White |
| EC809B | Black |



Dead End

Dead end cap for single and double circuit track


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP812W | White |
| EP812B | Black |



T-Bar Ceiling Feed

Live feed with outlet box for use with T-bar ceilings

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC817W | White |
| EC817B | Black |




Conduit Connector

To start a surface run

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC880W | White |
| EC880B | Black |


Two Circuit



Two Circuit Live-End Feed Connector with Current Limiter

1A to 12A available. Separate circuit breaker for each circuit. Custom current rating available upon request.

| CAT NO. | SPECIFICATIONS | CIRCUIT 1 | | CIRCUIT 2 | |
|---------|----------------|-----------|----------|-----------|----------|
| EC840W | White | 1A | 1 Amp | 1A | 1 Amp |
| EC840B | Black | 2A | 2.5 Amp | 2A | 2.5 Amp |
| | | 5A | 5 Amp | 5A | 5 Amp |
| | | 7A | 7.5 Amp | 7A | 7.5 Amp |
| | | 10A | 10 Amp | 10A | 10 Amp |
| | | 12A | 12.5 Amp | 12A | 12.5 Amp |




Two Circuit In-Line Feed Connector with Current Limiter

1A to 12A available. Separate circuit breaker for each circuit. Custom current rating available upon request.

| CAT NO. | SPECIFICATIONS | CIRCUIT 1 | | CIRCUIT 2 | |
|---------|----------------|-----------|----------|-----------|----------|
| EC841W | White | 1A | 1 Amp | 1A | 1 Amp |
| EC841B | Black | 2A | 2.5 Amp | 2A | 2.5 Amp |
| | | 5A | 5 Amp | 5A | 5 Amp |
| | | 7A | 7.5 Amp | 7A | 7.5 Amp |
| | | 10A | 10 Amp | 10A | 10 Amp |
| | | 12A | 12.5 Amp | 12A | 12.5 Amp |


General



Track Adapter Trim

For use with standard 6" recessed housings. Allow track lamp holders to be used with recessed installations. Up to 150W Max. 7 1/2" O.D.


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP577W | White |
| EP577B | Black |



Outlet Box Cover

Outlet box cover. Screws not included. 5" x 5" x 1/8" x 1 1/4" Sq


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP800W | White |
| EP800B | Black |
| EP800BZ | Bronze |



Monopoint Canopy

Allows any lamp holder (300W MAX.) to be converted to canopy installation. For Line Voltage fixtures.


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP811W | White |
| EP811B | Black |
| EP811BZ | Bronze |
| EP811N | Nickel |



Sign Hanger

Sign Hanger with hook for single and double circuit track. Holds up to 25 lbs.

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP813W | White |
| EP813B | Black |
| EP813BZ | Bronze |
| EP813N | Nickel |



Outlet Adapter

Outlet Adapter for single circuit and two circuit track


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP814W | White |
| EP814B | Black |
| EP814BZ | Bronze |
| EP814N | Nickel |



Pendant Adapter

For single circuit and two circuit track with strain relief connector for cord or chain hung fixtures. Holds up to 35 lbs.


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP815W | White |
| EP815B | Black |
| EP815BZ | Bronze |
| EP815N | Nickel |



Round Monopoint Canopy

For Line Voltage fixtures. 4 5/8" O.D


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP819W | White |
| EP819B | Black |
| EP819BZ | Bronze |



Straight Channel

Provides support for straight connection points in suspended track system. Track sits inside the channel. 16 1/4" long. Support rails for tracks


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP844W | White |
| EP844B | Black |



L Channel

Support corner connection points in suspended track system. Track sits inside the channel. 16 1/4" long in each side. Support rails for tracks.


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP845W | White |
| EP845B | Black |



Dimmer Switch

Dimmer with ON/OFF switch. For Line Voltage fixtures. 150W MAX. For use with extension wands. Halogen lamps only


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP901W | White |
| EP901B | Black |



Clamp Cord and Plug

Clamp with 6 ft. cord and plug with female track connector for attaching a Line Voltage fixture.

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP903W | White |
| EP903B | Black |




48" Steel Stem

For additional pendant length. Includes coupling. Use with EP918, EP924, EP936, and EP948

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP904W | White |
| EP904B | Black |


General



T-Bar Attachment Clip

Allows track to be attached to inverted T-Bar ceiling. Order as follow: (2) clips for 2' or 4' track, (3) clips for 6' track, (4) clips for 8' or 12' track.


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP989B | Black |



Slope Ceiling Fixture Adapter

Allows use of extension wands on slope ceiling. 0°- 90°


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP906W | White |
| EP906B | Black |



Track Pendant Kit

Track pendant kit with 60" stainless steel cable. 1/16" stranded


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP960W | White |
| EP960B | Black |



Clamp Cord and Track Adapter

Connects to Line Voltage track. Includes female track connector for attaching a Line Voltage fixture.

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP907W | White |
| EP907B | Black |



Pendant Assembly

Suspends track from ceiling. Order as follow: (2) kits for 2' or 4' track, (3) kits for 6' track, (4) kits for 8' track, (5) kits for 12', (1) EP807 per feed.


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP918W | White \ 18" |
| EP924W | White \ 24" |
| EP936W | White \ 36" |
| EP948W | White \ 48" |
| EP918B | Black \ 18" |
| EP924B | Black \ 24" |
| EP936B | Black \ 36" |
| EP948B | Black \ 48" |



Sloped Ceiling Pendant Adapter

Sloped Ceiling Pendant adapter for use with EP918, EP924, EP936, and EP948.


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP905W | White |
| EP905B | Black |



Wire Cover

Wire cover for power feed through with pendant assembly. One per run. For use with EP918 to EP948

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP807W | White |
| EP807B | Black |
| EP807BZ | Bronze |
| EP807N | Nickel |



Extension Wand

Line voltage extension wands. Drops head from track.

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP881W | 6" |
| EP882W | 12" |
| EP818W | 18" |
| EP824W | 24" |
| EP836W | 36" |
| EP848W | 48" |
| EP881B | 6" |
| EP882B | 12" |
| EP818B | 18" |
| EP824B | 24" |
| EP836B | 36" |
| EP848B | 48" |