

4" LED Light Engine with Trimless Reflector

The perfect lighting solution for high-end residential and light commercial projects.



Features

- High efficacy LED module.
- Triac/ELV/0-10V dimming.
- Must be used with ELCO 4" Cedar™ System Housings.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.
- Spackle frame included.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

| | |
|----------------------|--------|
| Wattage | 8.76W |
| Lumens | 850 lm |
| Color Temp. | 4000K |
| Lamp Type | LED |
| Beam Angle | 60° |
| CRI | 93+ |
| Damp Location | Listed |

Options



Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Trim Construction: Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.

Installation: Must be installed on a Cedar™ System housing with compatible lumen rating. Frames are available for New Construction and Remodel as IC or non-IC.


LED Technology:

- Extremely accurate Color Rendering Index of 93+.
- Efficacy of 97 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixilation.

Listings:

- UL Listed for Wet Location.
- RoHS Compliant.

Dimension



Spackle Frame Included



Product Number Builder Example: E430C0827W2

| ELCO 4" Trimless Reflector | Lumens | Color Temp. | Finish | Generation |
|----------------------------|--|---|--|----------------------------------|
| E430C | 08 850 lm 12 1250 lm 16 1600 lm | 27 2700K 30 3000K 35 3500K | W All White BZ All Bronze B All Black | 1 Gen 1 2 Gen 2 |

40 4000K
50 5000K
SD Sunset

For use with 4" Cedar™ Trimless Light Engines

4" Cedar™ Dedicated Trimless LED ICA Housings



4" IC Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| E4TL | Up to 1600lm |

PRODUCT NUMBER BUILDER

| Housing Type | Lumen | IC Airtight | Dimming | Optional |
|--------------|--|-------------|---|---|
| E4TL | 08 850 lm 12 1250 lm 16 1600 lm | ICA | (Blank) 120V Triac/ELV D 120/277V Triac/ELV/0-10V SD Sunset L Lutron | EM1 Emergency Backup up to 700 lm EM2 Emergency Backup up to 1100 lm |