ELCO Lighting

Project name:

Fixture type:

Date:

6" LED Module & Driver with Baffle Trim

The perfect lighting solution for high-end residential projects with existing housings.



Features

- Module includes LED Module Driver.
- Triac/ELV dimming.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.
- Title 24 JA8-2019 Compliant

Specifications


Wattage	15.7W
Lumens	1250 lm
Voltage	120V
Color Temp.	SunsetK
Dimmable	Triac/ELV
Lamp Type	LED
Beam Angle	60°
CRI	93+
Wet Location	Listed

Options



All White **Black w/White ring** **All Bronze**

Dimensions



Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Trim Construction: Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.

Compatible Housings: EL770ICA, EL770RICA.

LED Technology:

- Extremely accurate Color Rendering Index of 93+.
- Efficacy of 97 lumens per watt.
- Lumen Maintaince of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixelation.

Listings:

- UL Listed for Wet Location.
- RoHS Compliant.
- Title 24 JA8-2019 Compliant.

Product Number Builder Example: **E614R0827W**

ELCO 6" Baffle	Lumens	Color Temp.	Finish
E614R			
	08 850 lm	**27** 2700K	**W** All White
	12 1250 lm	**30** 3000K	**B** Black w/White Ring
		35 3500K	**BZ** All Bronze

2042 E. Vernon Ave., Vernon, CA 90058 • Tel (323) 231-2600 Fax (323) 231-3200 • elcolighting.com
© ELCO Lighting 2022. All rights reserved • Rev. 26 Jan 2022 • ELCO Lighting reserves the right to make specification and design changes without notice.


40 4000K
50 5000K
SD Sunset

© ELCO Lighting 2022. All rights reserved • Rev. 26 Jan 2022 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products


For use with **6″ Cedar™ LED Module & Driver**

6″ Dedicated LED ICA Housings



6″ IC Housing
New Construction


CAT NO.	SPECIFICATIONS
EL770ICA	24W MAX.



6″ ICA Housing
Remodel


CAT NO.	SPECIFICATIONS
EL770RICA	24W MAX.

6″ Accessories



Emergency Battery Backup

CAT NO.	SPECIFICATIONS
KEM-LD5	8W, 120/277V




Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 ⅜″ L x 14 ⅜″ W
FIREENCL-S	Shallow, 16″ L x 14 ⅜″ W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	¾″ W x 16′ L



Automatic Daylight Control Sensor

CAT NO.	SPECIFICATIONS
EADC1	For use with 0-10V frames.



Socket Adapter

CAT NO.	SPECIFICATIONS
PSA30	E26 to Quick Connect

© ELCO Lighting 2022. All rights reserved • Rev. 26 Jan 2022 • ELCO Lighting reserves the right to make specification and design changes without notice.